



## Series 25KA & Accessories



Page Tech Sheet **514**



**Temperature Range:**  
-20°C to +100°C  
Standard Seal NBR



**Maximum Static Working Pressure:**  
PB 35 bar (500 PSI)



Single Shut Off

**Interchangeability:**

Cejn 320

**Flow Rate:**

1800 L/Min

**Material:**

Brass Nickel Plated

**Application:**

General Purpose Pneumatic Coupling  
Euro Standard Design



Actual Size

Section 3 – Pneumatic QRC

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools


Tools, Hardware & PPE

### Couplings



**Male Thread, BSPT**

| 2510        |      |    |    |       |
|-------------|------|----|----|-------|
| 25KAAK13MPN | 1/4" | 19 | 60 | 20.70 |
| 25KAAK17MPN | 3/8" | 19 | 60 | 18.80 |
| 25KAAK21MPN | 1/2" | 22 | 61 | 20.00 |



**Female Thread, BSPP**

| 2510        |      |    |    |       |
|-------------|------|----|----|-------|
| 25KAIW13MPN | 1/4" | 19 | 56 | 18.80 |
| 25KAIW17MPN | 3/8" | 19 | 55 | 19.10 |
| 25KAIW21MPN | 1/2" | 24 | 58 | 22.20 |



**Hose Tail**

| 2510        | To Suit Hose I.D. |    |    |       |
|-------------|-------------------|----|----|-------|
| 25KATF06MPN | 6mm (1/4")        | 19 | 74 | 18.80 |
| 25KATF08MPN | 8mm (5/16")       | 19 | 74 | 18.80 |
| 25KATF09MPN | 9mm               | 19 | 74 | 19.00 |
| 25KATF10MPN | 10mm (3/8")       | 19 | 74 | 19.00 |
| 25KATF13MPN | 13mm (1/2")       | 19 | 74 | 19.70 |



**Quick Fit Tube Connection**

| 2510        | To Fit Tube Size mm |    |    |       |
|-------------|---------------------|----|----|-------|
| 25KAKO08MPN | 6 x 8               | 19 | 60 | 26.60 |



**Panel Mount, Standard Hose Tail**

| 2510        | To Suit Hose I.D. |    |    |       |
|-------------|-------------------|----|----|-------|
| 25KATS06MPN | 6mm (1/4")        | 19 | 76 | 30.85 |
| 25KATS08MPN | 8mm (5/16")       | 19 | 80 | 37.10 |
| 25KATS10MPN | 10mm (3/8")       | 19 | 87 | 36.65 |



**Quick Fit Tube Connection with Spring Guard**

| 2510        | To Fit Tube Size mm |    |     |       |
|-------------|---------------------|----|-----|-------|
| 25KAKK08MPN | 6 x 8               | 19 | 144 | 31.45 |
| 25KAKK10MPN | 8 x 10              | 19 | 155 | 31.45 |

Other materials, seals and finishes available on request, please contact our technical department for further details.