



## Series 25KA & Accessories



Page Tech Sheet **514**



**Temperature Range:**  
-20°C to +60°C  
Standard Seal NBR



**Maximum Static Working Pressure:**  
PB 35 bar (500 PSI)

**Interchangeability:**  
Rectus Design

**Material:**  
Brass Nickel Plated

**Application:**  
General Purpose Pneumatic Coupling

Section 3 – Pneumatic QRC

### Plugs



Male Thread, (Steel), BSPT

2510				£
25SFAK10SXN	1/8"	13	33	4.50
25SFAK13SXN	1/4"	14	37	4.30
25SFAK17SXN	3/8"	17	37	5.10
25SFAK21SXN	1/2"	22	43	10.05



Female Thread, (Steel), BSPP

2510				£
25SFIW10SXN	1/8"	14	30	4.50
25SFIW13SXN	1/4"	17	38.5	4.50
25SFIW17SXN	3/8"	19	39.5	5.20
25SFIW21SXN	1/2"	24	44	10.05



Hose Tail, (Steel)

2510	To Suit Hose I.D.		£
25SFTF06SXN	6mm (1/4")	48	4.30
25SFTF08SXN	8mm (5/16")	48	4.30
25SFTF09SXN	9mm	48	4.30
25SFTF10SXN	10mm (3/8")	48	4.30
25SFTF13SXN	13mm (1/2")	48	7.30



Quick Fit Tube Connection, (Brass)

2510	To Fit Tube Size mm		£
25SFKO06MXN	4 x 6	34	7.15
25SFKO08MXN	6 x 8	34	7.60
25SFKO10MXN	8 x 10	42	9.65
25SFKO12MXN	9 x 12	42	10.00



Panel Mount, Standard Hose Barb, (Brass)

2510	To Suit Hose I.D.			£
25SFTS06MXN	6mm (1/4")	14	56	21.55
25SFTS08MXN	8mm (5/16")	14	56	12.30
25SFTS10MXN	10mm (3/8")	17	56	12.60



Quick Fit Tube Connection with Spring Guard, (Brass)

2510	To Fit Tube Size mm		£
25SFKK06MXN	4 x 6	111	10.95

### Y Connector



2 x Coupling Outlets, 1 x Plug Inlet

2510		£
25Y	114	41.45

### Triple Outlet Connectors



3 x Coupling Outlets, 1 x 3/8" BSPP Inlet

2510		£
25W	119	67.70



3 x Coupling Outlets, 1 x 1/4" BSPP Inlet

2510		£
M3-25		59.20

Other materials, seals and finishes available on request, please contact our technical department for further details.