



## Series 25KA & Accessories



### Free Angle Rotating Joint



BSPT, Male

2510		
25FAAK13SPN	1/4"	74.60



BSPP Male x BSPP Female Thread

2510		
FA13A13ISPN	1/4"	41.60
FA17A17ISPN	3/8"	97.80

This rotating joint, when installed between the airline and hand tool, reduces operator wrist and elbow strain. It also acts as a universal joint and prevents kinks appearing in the airline.

### Recoil Eliminator (Anti-Whip)



Hose Connection, (Steel)

2510				
25SRTF06SXN	6mm (1/4")	21	60	20.00
25SRTF10SXN	10mm (3/8")	21	60	24.50
25SRTF13SXN	13mm (1/2")	21	60	18.35

### Leader Hoses

A 'Leader Hose' is a length of flexible hose which should be fitted between an air tool & the connecting coupling. By absorbing the impact of a pneumatic impact tool, a leader hose will significantly increase the life expectancy of the coupling.



3/8" Bore Rubber-Tech Hose, Plug One End, Thread One End, BSPT Male

2510			
LH25/13K	1/4"	381	16.30
LH25/17K	3/8"	381	17.95

**WARNING - Leader Hoses**

The Health & Safety Executive guide states - "the plug should not be screwed directly into the inlet port, but should be fitted onto a short isolation hose, thus isolating the plug & coupling from the tool vibration".

**AEROPRO**  
ENGINEERED FOR PROFESSIONALS

For  
**PNEUMATIC  
POWER TOOLS**  
see pages  
1426-1431

- Hydraulics
- Hydraulic QRC
- Pneumatic QRC**
- Ind. Air Prep, Monitor & Test
- KELM™ Pneumatics
- Pneumatic & Vacuum Equipment
- Valves
- Ring Main Systems
- Adaptors & Fittings
- Stainless Steel
- Malleable Iron
- Hose, Tubing & Couplings
- Clamps & Clips
- Sprays & Adhesives
- Blow Guns & Vacuum
- Wash Down & Fuelling
- Air Tools
- Tools, Hardware & PPE

Other materials, seals and finishes available on request, please contact our technical department for further details.