



## Series 25KE Self Venting



Page Tech Sheet **516**



**Temperature Range:**  
-20°C to +60°C  
Standard Seal NBR



**Maximum Static Working Pressure:**  
**Couplings:**  
PB 8 bar (116 PSI)



Single Shut Off

**Interchangeability:**  
Rectus Design

**Material:**  
Brass Nickel Plated  
**Application:**  
General Purpose Pneumatic Coupling  
Self-Venting Safety Feature  
EN 983 ISO 4414 ISO 6150



Actual Size

### Couplings



Male Thread, BSPT

2510				£
25KEAK13SPN	1/4"	24	62	48.80
25KEAK21SPN	1/2"	24	67	51.35



Female Thread, BSPP

2510				£
25KEIW13SPN	1/4"	24	59	48.80
25KEIW17SPN	3/8"	24	56	55.20
25KEIW21SPN	1/2"	24	61	55.40



Hose Tail

2510	To Suit Hose I.D.			£
25KETF08SPN	8mm (5/16")	24	77	49.00
25KETF10SPN	10mm (3/8")	24	77	48.80
25KETF13SPN	13mm (1/2")	24	77	48.80

### Plugs



Male Thread, (Steel), BSPT

2510				£
25SFAK10SXN	1/8"	13	33	4.50
25SFAK13SXN	1/4"	14	37	4.30
25SFAK17SXN	3/8"	17	37	5.10
25SFAK21SXN	1/2"	22	43	10.05



Female Thread, (Steel), BSPP

2510				£
25SFIW10SXN	1/8"	14	30	4.50
25SFIW13SXN	1/4"	17	38.5	4.50
25SFIW17SXN	3/8"	19	39.5	5.20
25SFIW21SXN	1/2"	24	44	10.05



Hose Tail, (Steel)

2510	To Suit Hose I.D.		£
25SFTF06SXN	6mm (1/4")	48	4.30
25SFTF08SXN	8mm (5/16")	48	4.30
25SFTF09SXN	9mm	48	4.30
25SFTF10SXN	10mm (3/8")	48	4.30
25SFTF13SXN	13mm (1/2")	48	7.30

Other materials, seals and finishes available on request, please contact our technical department for further details.

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE