



Series 25KS Safety Lock



Page Tech Sheet **519**



Temperature Range:
-20°C to +100°C
Standard Seal NBR



Maximum Static Working Pressure:
PB 35 bar (500 PSI)



Single Shut Off

Interchangeability:
Rectus Design

Material:
Brass Nickel Plated, Buna Seal
(Standard Series Coupling)

Application:
Two Handed Disconnection Prevents
Accidental Disconnection. The Coupling
and Plug Must Firstly be Pushed Together
Before the Sleeve is Pulled Back



Actual Size

Couplings



Male Thread, BSPT

2510				£
25KSAK13SPN	1/4"	19	60	62.20
25KSAK17SPN	3/8"	19	60	62.20
25KSAK21SPN	1/2"	22	61	63.75



Female Thread, BSPP

2510				£
25KSIW13SPN	1/4"	19	56	62.20
25KSIW17SPN	3/8"	19	55	62.20
25KSIW21SPN	1/2"	24	58	63.75



Hose Tail

2510	To Suit Hose I.D.			£
25KSTF08SPN	8mm (5/16")	19	74	62.20
25KSTF10SPN	10mm (3/8")	19	74	62.20
25KSTF13SPN	13mm (1/2")	19	74	63.75

Plugs



Male Thread, BSPT

2510				£
25SSAK13SXN	1/4"	14	37	9.15
25SSAK17SXN	3/8"	17	37	9.15
25SSAK21SXN	1/2"	22	43	23.05



Female Thread, BSPP

2510				£
25SSIW13SXN	1/4"	17	33	9.15
25SSIW17SXN	3/8"	19	33	10.40



Hose Tail

2510	To Suit Hose I.D.		£
25SSTF08SXN	8mm (5/16")	48	17.35
25SSTF10SXN	10mm (3/8")	48	17.75
25SSTF13SXN	13mm (1/2")	48	10.05

Other materials, seals and finishes available on request, please contact our technical department for further details.

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE