



## Series 25KA Stainless Steel



Page Tech Sheet **518**



**Temperature Range:**  
-15°C to +200°C  
Standard Seal FKM



**Maximum Static Working Pressure:**  
PB 35 bar (500 PSI)



Single Shut Off

**Interchangeability:**  
Cejn 320, Rectus 26

**Material:**  
Stainless Steel Coupling and Plug

**Application:**  
General Purpose Pneumatic Coupling, Stainless Steel



Actual Size

Section 3 – Pneumatic QRC



### Couplings



Male Thread, BSPP

2510	mm	L mm	£	
25KAAW13RVX	1/4"	19	59	269.95
25KAAW17RVX	3/8"	19	57.5	269.95



Female Thread, BSPP

2510	mm	L mm	£	
25KAIW13RVX	1/4"	19	56	269.95
25KAIW17RVX	3/8"	19	55	269.95
25KAIW21RVX	1/2"	24	56	289.60



Hose Tail

2510	To Suit Hose I.D.	mm	L mm	£
25KATF10RVX	10mm (3/8")	19	74	278.25
25KATF13RVX	13mm (1/2")	19	74	293.55

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

### Plugs



Male Thread, BSPP

2510	mm	L mm	£	
25SFAW13RXX	1/4"	17	33.5	31.70
25SFAW17RXX	3/8"	19	33	33.00
25SFAW21RXX	1/2"	24	38	47.10



Female Thread, BSPP

2510	mm	L mm	£	
25SFIW13RXX	1/4"	17	38.5	33.00
25SFIW17RXX	3/8"	19	39.5	33.00
25SFIW21RXX	1/2"	24	44	44.85



Hose Tail

2510	To Suit Hose I.D.	L mm	£
25SFTF06RXX	6mm (1/4")	48	29.90
25SFTF08RXX	8mm (5/16")	48	28.70
25SFTF10RXX	10mm (3/8")	48	25.90
25SFTF13RXX	13mm (1/2")	48	37.90

Other materials, seals and finishes available on request, please contact our technical department for further details.