



## Series 25KD Push-Type



**Temperature Range:**  
-20°C to +100°C  
Standard Seal NBR

**Maximum Static Working Pressure:**  
PB 35 bar (500 PSI)



**Interchangeability:**  
Rectus Design  
**Flow Rate:**  
Double Valved 710 L/Min

**Material:**  
Brass Nickel Plated  
**Application:**  
General Purpose Pneumatic Coupling



Actual Size

### ULTRA-FLO »»

### Couplings (Valved)



Male Thread, BSPT

2510				
25KDAK13BPNS	1/4"	19	60	71.10
25KDAK17BPNS	3/8"	19	60	71.10
25KDAK21BPNS	1/2"	22	61	71.20



Female Thread, BSPP

2510				
25KDIW13BPNS	1/4"	19	56	71.10
25KDIW17BPNS	3/8"	19	55	71.10
25KDIW21BPNS	1/2"	24	58	71.20



Hose Tail


2510	To Suit Hose I.D.			
25KDTF06BPNS	6mm (1/4")	19	74	71.10
25KDTF08BPNS	8mm (5/16")	19	74	71.10
25KDTF10BPNS	10mm (3/8")	19	74	187.35
25KDTF13BPNS	13mm (1/2")	19	74	74.40

### Plugs (Valved)



Male Thread, BSPP

2510				
25SDAW13MPN	1/4"	22	43	24.80
25SDAW17MPN	3/8"	22	43	24.80
25SDAW21MPN	1/2"	22	46	26.55



Female Thread, BSPP

2510				
25SDIW13MPN	1/4"	22	43	24.80
25SDIW17MPN	3/8"	22	43	24.80
25SDIW21MPN	1/2"	24	46	26.55



Hose Tail

2510	To Suit Hose I.D.			
25SDTF06MPN	6mm (1/4")	21	60	25.70
25SDTF08MPN	8mm (5/16")	21	60	25.70
25SDTF10MPN	10mm (3/8")	21	60	25.80
25SDTF13MPN	13mm (1/2")	21	60	26.70

Other materials, seals and finishes available on request, please contact our technical department for further details.

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE