



## Series 26KA & Accessories



Page Tech Sheet **520**



**Temperature Range:**  
-20°C to +100°C  
Standard Seal NBR



**Maximum Static Working Pressure:**  
PB 35 bar (500 PSI)



Single Shut Off

**Interchangeability:**  
Cejn 320, Festo KD Series

**Material:**  
Brass

**Application:**  
General Purpose Pneumatic Coupling



Actual Size

Section 3 – Pneumatic QRC

### Couplings



Hydraulics	Male Thread, BSPP				
Hydraulic QRC	2610				
Pneumatic QRC	26KAAW10MPX	1/8"	22	43	19.90
	26KAAW13MPX	1/4"	22	39	9.40
	26KAAW17MPX	3/8"	22	41	10.10
Ind. Air Prep., Monitor & Test	26KAAW21MPX	1/2"	22	44	10.15

Hydraulics	Female Thread, BSPP				
Hydraulic QRC	2610				
Pneumatic QRC	26KAIW13MPX	1/4"	22	41	10.10
	26KAIW17MPX	3/8"	22	41	10.10
	26KAIW21MPX	1/2"	24	44	10.15

Hydraulics	Hose Tail				
Hydraulic QRC	2610				
Pneumatic QRC	26KATF06MPX	To Suit Hose I.D.	6mm (1/4")	21	58
	26KATF08MPX		8mm (5/16")	21	58
	26KATF09MPX		9mm	21	58
	26KATF10MPX		10mm (3/8")	21	58
	26KATF13MPX		13mm (1/2")	21	58

### Plugs



All of the above plugs will connect with the Series 25 Couplings.



Hydraulics	Male Thread, BSPP				
Hydraulic QRC	2610				
Pneumatic QRC	25SFAW10MXX	1/8"	14	31	4.55
	25SFAW13MXX	1/4"	17	33	4.00
	25SFAW17MXX	3/8"	19	33	2.65
Ind. Air Prep., Monitor & Test	25SFAW21MXX	1/2"	24	38	4.20

Hydraulics	Female Thread, BSPP				
Hydraulic QRC	2610				
Pneumatic QRC	25SFIW10MXX	1/8"	14	30	2.60
	25SFIW13MXX	1/4"	17	33	2.60
	25SFIW17MXX	3/8"	19	33	2.65
Ind. Air Prep., Monitor & Test	25SFIW21MXX	1/2"	24	35	4.40

Hydraulics	Hose Tail				
Hydraulic QRC	2610				
Pneumatic QRC	25SFTF06MXX	To Suit Hose I.D.	6mm (1/4")	48	1.90
	25SFTF08MXX		8mm (5/16")	48	1.95
	25SFTF09MXX		9mm	48	1.95
	25SFTF10MXX		10mm (3/8")	48	2.20
	25SFTF13MXX		13mm (1/2")	48	2.60

### Y Connector



### Triple Outlet Connector



2 x Coupling Outlets,  
1 x Plug Inlet

3 x Coupling Outlets,  
1 x 3/8" BSPP Inlet

Hydraulics			
Hydraulic QRC	2610		
Pneumatic QRC	26Y	90	27.30

Hydraulics			
Hydraulic QRC	2610		
Pneumatic QRC	26W	96	48.80

Other materials, seals and finishes available on request, please contact our technical department for further details.