



Series 26KE Self Venting



Page Tech Sheet **10281**



Temperature Range:
-20°C to +60°C
Standard Seal NBR



Maximum Static Working Pressure:
PB 12 bar (174 PSI)



Single Shut Off

Interchangeability:
Rectus Design



EN 983
ISO 4414
ISO 6150

Material:
Brass Nickel Plated

Application:
General Purpose Pneumatic Coupling
Self-Venting Safety Feature



Actual Size

Section 3 – Pneumatic QRC

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

Couplings



Male Thread, BSPP

2610		mm	L mm	£
26KEAW13MPN	1/4"	22	55	25.70
26KEAW17MPN	3/8"	22	55	25.80
26KEAW21MPN	1/2"	24	58	26.95



Female Thread, BSPP

2610		mm	L mm	£
26KEIW13MPN	1/4"	22	57	26.15
26KEIW17MPN	3/8"	22	57	28.00
26KEIW21MPN	1/2"	24	60	26.70



Hose Tail

2610	To Suit Hose I.D.	mm	L mm	£
26KETF06MPN	6mm (1/4")	22	71	24.90
26KETF09MPN	9mm	22	71	26.05
26KETF10MPN	10mm (3/8")	22	71	26.35
26KETF13MPN	13mm (1/2")	22	71	25.05

Plugs



Male Thread, (Steel), BSPT

2510		mm	L mm	£
25SFAK10SXN	1/8"	13	33	4.50
25SFAK13SXN	1/4"	14	37	4.30
25SFAK17SXN	3/8"	17	37	5.10
25SFAK21SXN	1/2"	22	43	10.05



Female Thread, (Steel), BSPP

2510		mm	L mm	£
25SFIW10SXN	1/8"	14	30	4.50
25SFIW13SXN	1/4"	17	38.5	4.50
25SFIW17SXN	3/8"	19	39.5	5.20
25SFIW21SXN	1/2"	24	44	10.05



Hose Tail, (Steel)

2510	To Suit Hose I.D.	L mm	£
25SFTF06SXN	6mm (1/4")	48	4.30
25SFTF08SXN	8mm (5/16")	48	4.30
25SFTF09SXN	9mm	48	4.30
25SFTF10SXN	10mm (3/8")	48	4.30
25SFTF13SXN	13mm (1/2")	48	7.30

Other materials, seals and finishes available on request, please contact our technical department for further details.