



Series 27KA




Page Tech Sheet 521



Temperature Range:
Couplings:
 -20°C to +100°C
 Standard Seal NBR
Plugs:
 -20°C to +60°C



Maximum Static Working Pressure:
 PB 35 bar (500 PSI)



Single Shut Off



Actual Size

Interchangeability:
 Cejn 410

Material:
 Brass, Nickel Plated, Buna Seal
 (Standard Series) Coupling

Application:
 General Purpose High-Flo Pneumatic
 Coupling Self Venting Safety Feature.
 Machinery Construction, Trade & Automotive

Couplings



Male Thread, BSPT

2710	mm	L mm	£	
27KAAK13MPN	1/4"	24	63	36.75
27KAAK17MPN	3/8"	24	63	36.60
27KAAK21MPN	1/2"	24	65	45.40
27KAAK26MPN	3/4"	27	65	45.40



Female Thread, BSPP

2710	mm	L mm	£	
27KAIW13MPN	1/4"	24	56	45.95
27KAIW17MPN	3/8"	24	56	45.95
27KAIW21MPN	1/2"	24	56	43.90
27KAIW26MPN	3/4"	27	60	42.10



Hose Tail

2710	To Suit Hose I.D.	mm	L mm	£
27KATF06MPN	6mm (1/4")	24	76	41.30
27KATF09MPN	9mm	24	76	41.60
27KATF10MPN	10mm (3/8")	24	76	41.60
27KATF13MPN	13mm (1/2")	24	76	42.10
27KATF16MPN	16mm (5/8")	24	76	42.10
27KATF19MPN	19mm (3/4")	24	76	41.60

Plugs



Male Thread, BSPT

2710	mm	L mm	£	
27SFAK13SXN	1/4"	17	40	10.30
27SFAK17SXN	3/8"	17	40	10.30
27SFAK21SXN	1/2"	22	45	11.00
27SFAK26SXN	3/4"	27	48	14.40



Female Thread, BSPP

2710	mm	L mm	£	
27SFIW13SXN	1/4"	17	33	11.00
27SFIW17SXN	3/8"	19	33	11.00
27SFIW21SXN	1/2"	24	37	11.00
27SFIW26SXN	3/4"	32	42	18.70



Hose Tail

2710	To Suit Hose I.D.	L mm	£
27SFTF06SXN	6mm (1/4")	48	6.45
27SFTF09SXN	9mm	48	6.45
27SFTF10SXN	10mm (3/8")	48	6.45
27SFTF13SXN	13mm (1/2")	48	6.45
27SFTF16SXN	16mm (5/8")	48	8.95
27SFTF19SXN	19mm (3/4")	48	10.20

Other materials, seals and finishes available on request, please contact our technical department for further details.

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE