



Series 27KB




Page Tech Sheet 522



Temperature Range:
-20°C to +100°C
Standard Seal NBR



Maximum Static Working Pressure:
PB 35 bar (500 PSI)



Double Shut Off

Interchangeability:
Rectus Design

Material:
Brass

Application:
General Purpose High-Flo Pneumatic Coupling



Actual Size

Section 3 – Pneumatic QRC

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

Couplings



Male Thread, BSPT

0194				£
27KBAK21BPX	1/2"	24	65	84.75



Female Thread, BSPP

0194				£
27KBIW17BPX	3/8"	24	56	84.75
27KBIW21BPX	1/2"	24	56	84.75
27KBIW26BPX	3/4"	32	60	87.75



Hose Tail

0194	To Suit Hose I.D. (mm)			£
27KBTF10BPX	10	24	76	85.40
27KBTF13BPX	13	24	76	85.40
27KBTF19BPX	19	24	76	86.00

Plugs



Male Thread, BSPT

0194				£
27SBAK21MPX	1/2"	24	62.5	51.85
27SBAK26MPX	3/4"	27	62.5	53.00



Female Thread, BSPP

0194				£
27SBIW21MPX	1/2"	24	54.5	51.85
27SBIW26MPX	3/4"	32	58.5	53.00



Hose Tail

0194	To Suit Hose I.D.			£
27SBTF13MPX	13mm (1/2")	24	74	54.50
27SBTF19MPX	19mm (3/4")	24	74	58.10

Other materials, seals and finishes available on request, please contact our technical department for further details.