



## Series 27KE



### Page Tech Sheet 799



**Temperature Range:**  
-20°C to +60°C  
Standard Seal NBR



**Maximum Static Working Pressure:**  
PB 12 bar (174 PSI)



Single Shut Off

**Material:**

Brass, Nickel Plated, Buna Seal (Standard Series) Coupling

**Application:**

General Purpose Pneumatic Coupling Self Venting Safety Feature.  
Machinery Construction, Trade & Automotive



Actual Size

Section 3 – Pneumatic QRC

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

### Couplings



Male Thread, BSPP

0194				£
27KEAK17MPN	3/8"	27	79	170.90
27KEAK21MPN	1/2"	27	80.5	170.90
27KEAK26MPN	3/4"	32	86	170.90



Female Thread, BSPP

0194				£
27KEIW17MPN	3/8"	27	83	170.90
27KEIW21MPN	1/2"	27	84	191.40
27KEIW26MPN	3/4"	32	86	170.90

### Plugs



Male Thread, BSPT

2710				£
27SFAK13SXN	1/4"	17	40	10.30
27SFAK17SXN	3/8"	17	40	10.30
27SFAK21SXN	1/2"	22	45	11.00
27SFAK26SXN	3/4"	27	48	14.40



Female Thread, BSPP

2710				£
27SFIW13SXN	1/4"	17	33	11.00
27SFIW17SXN	3/8"	19	33	11.00
27SFIW21SXN	1/2"	24	37	11.00
27SFIW26SXN	3/4"	32	42	18.70



Hose Tail

2710	To Suit Hose I.D.		£
27SFTF06SXN	6mm (1/4")	48	6.45
27SFTF09SXN	9mm	48	6.45
27SFTF10SXN	10mm(3/8")	48	6.45
27SFTF13SXN	13mm (1/2")	48	6.45
27SFTF16SXN	16mm (5/8")	48	8.95
27SFTF19SXN	19mm (3/4")	48	10.20

Other materials, seals and finishes available on request, please contact our technical department for further details.