



Series 30KA



Page Tech Sheet **800**



Temperature Range:
-20°C to +100°C
Standard Seal NBR



Maximum Static Working Pressure:
PB 35 bar (500 PSI)



Single Shut Off

Interchangeability:
US-MIL-SPEC-C-4109
ISO 615oB, Gromelle 900
Aro, Hansen 4000,
Parker 30 3/8"

Material:
Brass, Nickel Plated, Buna Seal
(Standard Series) Coupling

Application:
General Purpose Pneumatic Coupling,
Machinery Construction, Trade & Automotive



Actual Size

Section 3 – Pneumatic QRC

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

Couplings



Male Thread, BSPP

3710				£
30KAAW13SPN	1/4"	22	49	37.40
30KAAW17SPN	3/8"	22	49	37.40
30KAAW21SPN	1/2"	22	52	38.00



Female Thread, BSPP

3710				£
30KAIW13SPN	1/4"	22	49	37.40
30KAIW17SPN	3/8"	22	49	37.40
30KAIW21SPN	1/2"	22	52	38.00



Hose Tail

3710	To Suit Hose I.D.			£
30KATF06SPN	6mm (1/4")	21	66	38.75
30KATF08SPN	8mm (5/16")	21	66	38.75
30KATF10SPN	10mm (3/8")	21	66	38.75
30KATF13SPN	13mm (1/2")	21	66	38.75

Plugs



Male Thread, BSPP

3710				£
30SFAW13SXN	1/4"	17	42	12.30
30SFAW17SXN	3/8"	19	42	12.70
30SFAW21SXN	1/2"	24	46	13.30



Female Thread, BSPP

3710				£
30SFIW13SXN	1/4"	17	40	12.30
30SFIW17SXN	3/8"	19	42	12.70
30SFIW21SXN	1/2"	24	43	13.30



Hose Tail

3710	To Suit Hose I.D.		£
30SFTF06SXN	6mm (1/4")	55	12.35
30SFTF08SXN	8mm (5/16")	55	12.35
30SFTF10SXN	10mm (3/8")	55	12.35
30SFTF13SXN	13mm (1/2")	55	12.35

Other materials, seals and finishes available on request, please contact our technical department for further details.