



Series 33KA



Page Tech Sheet 523



Temperature Range:
-20°C to +100°C
Standard Seal NBR



Maximum Static Working Pressure:
PB 35 bar (500 PSI)



Single Shut Off

Interchangeability:
Atlas QIC 10

Material:
Steel Nickel Plated
Application:
General Purpose High-Flo Pneumatic Coupling



Actual Size

Couplings



Male Thread, BSPT

3310				£
33KAAK13SPN	1/4"	19	60	31.80
33KAAK17SPN	3/8"	19	59	31.80
33KAAK21SPN	1/2"	22	60	34.10



Female Thread, BSPP

3310				£
33KAIW13SPN	1/4"	19	55	31.10
33KAIW17SPN	3/8"	19	54	31.10
33KAIW21SPN	1/2"	24	57	34.10



Hose Tail

3310	To Suit Hose I.D.			£
33KATF06SPN	6mm (1/4")	19	73	31.10
33KATF08SPN	8mm (5/16")	19	73	31.10
33KATF10SPN	10mm (3/8")	19	73	31.10
33KATF13SPN	13mm (1/2")	19	73	32.25

Plugs



Male Thread, BSPT

3310				£
33SFAK13SXN	1/4"	14	42	7.20
33SFAK17SXN	3/8"	17	42	7.20
33SFAK21SXN	1/2"	22	47	13.15



Female Thread, BSPP

3310				£
33SFIW13SXN	1/4"	17	37	7.20
33SFIW17SXN	3/8"	17	37	7.20
33SFIW21SXN	1/2"	24	42	9.10



Hose Tail

3310	To Suit Hose I.D.		£
33SFTF06SXN	6mm (1/4")	52	10.15
33SFTF08SXN	8mm (5/16")	52	10.10
33SFTF10SXN	10mm (3/8")	52	10.10
33SFTF13SXN	13mm (1/2")	52	10.25

Other materials, seals and finishes available on request, please contact our technical department for further details.

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE