



Series 34KA



Page Tech Sheet **524**



Temperature Range
-20°C to +100°C
Standard Seal NBR



Maximum Static Working Pressure:
PB 35 bar (500 PSI)



Single Shut Off

Interchangeability:
Atlas Copco QIC 15

Material:
Steel Nickel Plated

Application:
General Purpose Pneumatic Coupling



Actual Size

Section 3 – Pneumatic QRC

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

Couplings



Male Thread, BSPT

3310				£
34KAAK17SPN	3/8"	24	70	61.25
34KAAK21SPN	1/2"	24	72	61.25
34KAAK26SPN	3/4"	27	72	70.25



Female Thread, BSPP

3310				£
34KAIW13SPN	1/4"	24	64	61.25
34KAIW21SPN	1/2"	24	64	61.25
34KAIW26SPN	3/4"	32	68	70.25



Hose Tail

3310	To Suit Hose I.D.			£
34KATF10SPN	10mm (3/8")	24	84	61.25
34KATF13SPN	13mm (1/2")	24	84	61.25

Plugs



Male Thread, BSPT

3310				£
34SFAK17SXN	3/8"	19	46	10.25
34SFAK21SXN	1/2"	22	52	10.25



Female Thread, BSPP

3310				£
34SFIW17SXN	3/8"	19	40	10.25
34SFIW21SXN	1/2"	24	44	11.80



Hose Tail

3310	To Suit Hose I.D.		£
34SFTF06SXN	6mm (1/4")	55	10.25
34SFTF10SXN	10mm (3/8")	55	10.25
34SFTF13SXN	13mm (1/2")	55	10.25

Other materials, seals and finishes available on request, please contact our technical department for further details.