



Series 41KF Water Couplings



Page Tech Sheet **525**



Temperature Range:
-20°C to +100°C
Standard Seal NBR



Maximum Static Working Pressure:
PB 35 bar (500 PSI)



Straight Through



Actual Size

Interchangeability:
Cejn 4170

Material:
Steel Nickel Plated

Application:
Straight Through Coupling Designed for Water

Couplings



Male Thread, BSPP

4110			£
41KFAW21MPN	1/2"	31	19.70
41KFAW26MPN	3/4"	32	33.10



Female Thread, BSPP & Metric

4110				£
41KFIW21MPN	1/2"	24	32	20.30
41KFIW26MPN	3/4"	30	32	36.30
41KFIW22MPN	M22	24	32	25.05



Hose Tail

4110	To Suit Hose I.D.		£
41KFTF10MPN	10mm (3/8")	48	20.65
41KFTF13MPN	13mm (1/2")	48	20.65
41KFTF16MPN	16mm (5/8")	48	24.40
41KFTF19MPN	19mm (3/4")	48	27.70

Plugs



Male Thread, BSPP

4110				£
41SFAW21MXN	1/2"	24	40	14.35
41SFAW26MXN	3/4"	32	45	17.50



Female Thread, BSPP

4110				£
41SFIW21MXN	1/2"	24	37	24.40
41SFIW26MXN	3/4"	32	42	27.70



Hose Tail

4110	To Suit Hose I.D.		£
41SFTF10MXN	10mm (3/8")	48	9.20
41SFTF13MXN	13mm (1/2")	48	9.20
41SFTF16MXN	16mm (5/8")	48	12.90
41SFTF19MXN	19mm (3/4")	48	13.75

For **Wash Down Guns**
see pages 1362-1363



Other materials, seals and finishes available on request, please contact our technical department for further details.

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE