



Series 45KF Water Couplings Manual Type



Page Tech Sheet **10282**



Temperature Range:
-20°C to +100°C
Standard Seal NBR



Maximum Static Working Pressure:
PB 150 bar (2,140 PSI)



Straight Through



Actual Size

Interchangeability:
Hanson, Parker

Material:
Brass, Steel

Application:
Straight Through Coupling, Maximum Flow,
High Pressure Water and Steam Washers


Section 3 – Pneumatic QRC

Couplings



Brass with Stainless Balls & Springs complete with Viton Seals, Female Thread, BSPP

4510			
45KFIW17MVX	3/8"	37	34.10



Brass with Stainless Balls & Springs complete with Viton Seals, Male Thread, BSPP


4510			
45KFAW17MVX	3/8"	43	41.80

Plugs



Mild Steel, Case Hardened & Nickel Plated, Female Thread, BSPP

4510			
45SFIW17SXN	3/8"	40	15.90



Mild Steel, Case Hardened & Nickel Plated, Male Thread, BSPP

4510			
45SFAW17SXN	3/8"	42	21.60



For Pressure Washer Lances
see page 1371



Other materials, seals and finishes available on request, please contact our technical department for further details.

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE