



## Series 51KB



Page Tech Sheet **2099**



**Temperature Range:**  
-20°C to +100°C  
Standard Seal NBR



**Maximum Static Working Pressure:**  
PB 50 bar (725 PSI)



Single Shut Off



Double Shut Off

**Interchangeability:**  
Rectus Design

**Material:**  
Brass Nickel Plated

**Application:**  
Robust Steel Coupling for  
Compressed Air



Actual Size

### Couplings



Male Thread, BSPP



Part No.	Size	mm	L mm	£
51KBAW13SPN	1/4"	22	61	24.75
51KBAW17SPN	3/8"	22	61	24.75
51KBAW21SPN	1/2"	22	61	24.75



Female Thread, BSPP



Part No.	Size	mm	L mm	£
51KBIW13SPN	1/4"	22	61	24.75
51KBIW17SPN	3/8"	22	61	29.00
51KBIW21SPN	1/2"	22	61	25.55



Hose Tail



Part No.	To Suit Hose I.D. mm	mm	L mm	£
51KBTf06SPN	6	21	78	25.50
51KBTf09SPN	9	21	78	25.50
51KBTf13SPN	13	21	78	25.90

### Plugs



Male Thread, BSPP



Part No.	Size	mm	L mm	£
51SFAW13SXN	1/4"	17	35	5.20
51SFAW17SXN	3/8"	19	36	5.20



Female Thread, BSPP



Part No.	Size	mm	L mm	£
51SFIW13SXN	1/4"	17	34	7.20
51SFIW17SXN	3/8"	19	34	6.20



Hose Tail



Part No.	To Suit Hose I.D. mm	mm	L mm	£
51SBTF06SPN	6	21	65.5	20.90
51SBTF09SPN	9	21	65.5	20.90
51SBTF11SPN	11	21	65.5	20.90
51SBTF13SPN	13	21	65.5	20.90

Other materials, seals and finishes available on request, please contact our technical department for further details.

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE