



Series 52KB



Page Tech Sheet **2100**




Temperature Range:
-20°C to +100°C
Standard Seal NBR



Maximum Static Working Pressure:
PB 50 bar (725 PSI)



Single Shut Off



Double Shut Off

Interchangeability:
Rectus Design

Material:
Brass Nickel Plated, Buna Seal

Application:
Robust Steel Coupling for Compressed Air



Actual Size

Section 3 – Pneumatic QRC

Couplings

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE



Male Thread, BSPP

0194



52KBAW13SPN	1/4"	22	62	26.45
52KBAW17SPN	3/8"	22	62	26.45
52KBAW21SPN	1/2"	22	65	26.45



Female Thread, BSPP

0194



52KBIW13SPN	1/4"	22	62	26.45
52KBIW17SPN	3/8"	22	60	26.45
52KBIW21SPN	1/2"	22	65	26.45



Hose Tail

0194



52KBTf06SPN	6	21	79	27.40
52KBTf09SPN	9	21	80	27.40
52KBTf11SPN	11	21	80	27.80
52KBTf13SPN	13	21	79	27.80

Plugs



Male Thread, BSPP

0194



52SFAW17SXN	3/8"	35	5.55
-------------	------	----	------



Female Thread, BSPP

0194



52SFIW13SXN	1/4"	33	5.55
52SFIW17SXN	3/8"	33	8.05



Hose Tail

0194



52SFTf06SXN	6	46	5.85
52SFTf11SXN	11	53	6.10

Valved Plugs



Male Thread, BSPP

0194



52SBAW13SPN	1/4"	48	22.85
52SBAW17SPN	3/8"	48	22.85
52SBAW21SPN	1/2"	48	22.85

Other materials, seals and finishes available on request, please contact our technical department for further details.