




Series 57KB



Page Tech Sheet **2101**



Temperature Range:
-20°C to +100°C
Standard Seal NBR



Double Shut Off



Maximum Static Working Pressure:
PB 35 bar (500 PSI)

Interchangeability:
Rectus Design

Material:
Brass Nickel Plated, Buna Seal
Application:
Robust Steel Coupling for Compressed Air



Section 3 – Pneumatic QRC

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

Couplings



Male Thread, BSPP

0194



57KBAW26SPN	3/4"	34	100	110.70
57KBAW33SPN	1"	41	100	112.20



Female Thread, BSPP

0194



57KBIW21SPN	1/2"	34	100	110.70
57KBIW26SPN	3/4"	34	100	110.70
57KBIW33SPN	1"	41	101	112.20

Actual Size



Hose Tail

0194



57KBTf16SPN	16	34	122	113.50
57KBTf19SPN	19	34	122	114.60

Plugs



Male Thread, BSPP

0194



57SBAW17SPN	3/8"	86	73.10
57SBAW21SPN	1/2"	83	73.10
57SBAW26SPN	3/4"	85	75.20
57SBAW33SPN	1"	85	76.65



Female Thread, BSPP

0194



57SBIW21SPN	1/2"	85	75.20
57SBIW26SPN	3/4"	85	75.20



Hose Tail

0194



57SBTF13SPN	13	34	107	78.05
57SBTF16SPN	16	34	107	78.05
57SBTF19SPN	19	34	107	79.20

Other materials, seals and finishes available on request, please contact our technical department for further details.