






Series 68KA



 **Temperature Range:**
-10°C to +80°C
Standard Seal NBR

 **Maximum Static Working Pressure:**
PB 17 bar (246 PSI)



Interchangeability:
Schrader Heavy Duty

Material:
Steel Nickel Plated, Buna Seal
(Standard Series Coupling)

Application:
General Purpose Pneumatic Coupling







Actual Size

Couplings








Male Thread, BSPP

1710				
68KAAW17SPN	3/8"	30	66	37.75
68KAAW21SPN	1/2"	30	68	37.75
68KAAW26SPN	3/4"	30	68	42.55







Female Thread, BSPP

1710				
68KAIW13SPN	1/4"	30	74	36.60
68KAIW17SPN	3/8"	30	74	55.20
68KAIW21SPN	1/2"	30	68	38.85
68KAIW26SPN	3/4"	32	68	42.55







Hose Tail

1710				
68KATF10SPN	10mm (3/8")	30	81	54.75
68KATF13SPN	13mm (1/2")	30	81	42.85
68KATF19SPN	19mm (3/4")	30	81	42.85

Plugs








Male Thread, BSPT

1710				
68SFAK13SXN	1/4"	17	48	6.10
68SFAK17SXN	3/8"	22	50	6.10
68SFAK21SXN	1/2"	22	52	6.20
68SFAW26SXN	3/4"	27	53	6.10



Female Thread, BSPP

1710				
68SFIW13SXN	1/4"	18	43	6.10
68SFIW17SXN	3/8"	22	46	6.10



Hose Tail

1710				
68SFTF10SXN	10mm (3/8")	71	71	6.10
68SFTF13SXN	13mm (1/2")	67	67	6.10

Other materials, seals and finishes available on request, please contact our technical department for further details.

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE