



Series 83KA



Temperature Range:
-20°C to +100°C
Standard Seal NBR



Maximum Static Working Pressure:
PB 35 bar (500 PSI)



Single Shut Off

Interchangeability:
Hanson 5000,
Norgren Dynaquip,
US-MIL-NORM C4190 1/2"

Material:
Brass
Application:
Large Air Tools used in Heavy Industry



Actual Size

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

Couplings



Male Thread, BSPT

3710



83KAAK17MPG	3/8"	28	88	66.05
83KAAK21MPG	1/2"	28	93	66.05
83KAAK26MPG	3/4"	28	93	69.25



Female Thread, BSPP

3710



83KAIW17MPG	3/8"	28	88	66.05
83KAIW21MPG	1/2"	28	88	66.05
83KAIW26MPG	3/4"	28	86	69.25



Hose Tail

3710



83KATF13MPG	13mm (1/2")	28	102	69.25
83KATF19MPG	19mm (3/4")	28	102	69.25

Plugs



Male Thread, BSPT

3710



83SFAK17SXG	3/8"	17	53	13.75
83SFAK21SXG	1/2"	22	60	13.75
83SFAK26SXG	3/4"	27	61	15.40



Female Thread, BSPP

3710



83SFIW17SXG	3/8"	19	47	13.85
83SFIW21SXG	1/2"	24	50	13.85
83SFIW26SXG	3/4"	32	57	15.20



Hose Tail

3710



83SFTF10SXG	10mm (3/8")	62	12.45
83SFTF13SXG	13mm (1/2")	62	12.45
83SFTF19SXG	19mm (3/4")	62	15.00

Other materials, seals and finishes available on request, please contact our technical department for further details.