



Series 86KA & Accessories



Page Tech Sheet **527**



Temperature Range:
-15°C to +200°C
Standard Seal FKM



Maximum Static Working Pressure:
PB 15 bar (217 PSI)



Single Shut Off



Double Shut Off



Straight Through



Actual Size

Interchangeability:
D-M-E, Foster FJT,
Parker Mold Mate

Material:
Brass, Seals Viton Standard,
Silicone available

Application:
Brass Coupling for Connection of
Coolant Lines to Moulds and Dies

Section 3 – Pneumatic QRC

Couplings

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE



Male Thread, BSPP, Non-valved

4610				
86KFAW13MVX	1/4"	15	43	16.95

Male Thread, BSPP, Valved

4610				
86KBAW13MVX	1/4"	15	43	27.00



45° Hose Tail, Non-valved

4610				
86KFTH08MVX	8mm (5/16")	15	61	19.00

45° Hose Tail, Valved

4610				
86KBTH09MVX	9mm (3/8")	15	61	24.90



Female Thread, BSPP, Non-valved

4610				
86KFIW10MVX	1/8"	15	39	14.55
86KFIW13MVX	1/4"	15	41	14.55

Female Thread, BSPP, Valved

4610				
86KBIW13MVX	1/4"	15	41	20.30




90° Hose Tail, Non-valved

4610				
86KFTR09MVX	9mm (3/8")	15	44	19.00

90° Hose Tail, Valved

4610				
86KBTR09MVX	9mm (3/8")	15	44	24.90



Straight Hose Tail, Non-valved

4610				
86KFTF06MVX	6mm (1/4")	15	56	14.05
86KFTF09MVX	9mm (3/8")	15	56	14.05

Straight Hose Tail, Valved

4610				
86KBTF06MVX	6mm (1/4")	15	56	20.30
86KBTF08MVX	8mm (5/16")	15	56	20.30
86KBTF09MVX	9mm (3/8")	15	56	20.30

Other materials, seals and finishes available on request, please contact our technical department for further details.