



Series 'ST' Straight-Through Couplings



WORKING PRESSURE (PSI) SERIES 'ST'

Size	Steel Plug	Brass Plug	All Stainless
1/8"	2,600	2,500	4,200
1/4"	5,500	5,200	6,700
3/8"	3,500	2,700	5,500
1/2"	2,700	2,200	-
3/4"	1,700	1,700	-

Page Tech Sheet **535**



Temperature Range:
-40°C to +100°C

Standard Seals: Nitrile
Only couplings and plugs of the same size, will interchange.
Interchangeability: Hansen ST

Section 3 – Pneumatic QRC

Couplings



Brass, Male Thread, NPTF

8110			£
TB1S-10	1/8"	27	9.80
TB2S-15	1/4"	44	11.85
TB3S-20	3/8"	45	14.30
TB4S-25	1/2"	52	18.70
TB6S-30	3/4"	57	29.70

Plugs



Brass, Male Thread, NPTF

8110		£
TB1T-10	1/8"	2.95
TB2T-15	1/4"	3.20
TB3T-20	3/8"	5.80
TB4T-25	1/2"	7.05
TB6T-30	3/4"	12.40



Brass, Female Thread, NPTF

8110		£
TB1T-11	1/8"	3.05
TB2T-16	1/4"	4.60
TB3T-21	3/8"	6.10
TB4T-26	1/2"	7.20
TB6T-31	3/4"	13.35



Stainless Steel, Male Thread, NPTF

8110			£
T1S-10-303	1/8"	27	48.55
T2S-15-303	1/4"	44	73.20
T3S-20-303	3/8"	45	84.95



Steel, Male Thread, NPTF

8110		£
T1T-10	1/8"	9.80
T3T-20	3/8"	5.60
T4T-25	1/2"	5.50



Steel, Female Thread, NPTF

8110		£
T2T-16	1/4"	4.70
T3T-21	3/8"	6.00
T6T-31	3/4"	12.25



Brass, Female Thread, NPTF

8110			£
TB1S-11	1/8"	27	9.80
TB2S-16	1/4"	39	12.40
TB3S-21	3/8"	41	14.85
TB4S-26	1/2"	48	20.75
TB6S-31	3/4"	52	33.80



Stainless Steel, Male Thread, NPTF

8110		£
T1T-10-303	1/8"	20.85
T2T-15-303	1/4"	24.20



Stainless Steel, Female Thread, NPTF

8110			£
T1S-11-303	1/8"	27	45.00
T2S-16-303	1/4"	39	74.60