



Air Preparation



Working Temperature:
-20°C to +70°C



Maximum Working Pressure:
9 bar

Can be fitted to any combination units, fitted before the lubricator it can be used to port off a non-lubricated air supply that might be required for your system. These units are to be used in conjunction with Kelm™ Air Preparation, or as a stand alone BSPP manifold block.

When using with existing Kelm™ Air Preparation, you will also require additional fixing brackets.

200 Series Porting Blocks

These units are to be used in conjunction with Kelm™ Air Preparation, or as a stand alone BSPP manifold block.



BSPP

0338



£

KA200-06	1/8"	24.10
KA200-08	1/4"	24.10

400 Series Porting Blocks



BSPP

0338



£

KA400-10	3/8"	32.75
KA400-15	1/2"	32.75

300 Series Porting Blocks



BSPP

0338



£

KA300-08	1/4"	27.10
KA300-10	3/8"	27.10

600 Series Porting Blocks



BSPP

0338



£

KA600-20	3/4"	87.35
KA600-25	1"	87.35

Fixing Brackets



U Style Brackets

0338



£

KA200U-P1	200	13.50
KA300U-P1	300	14.60
KA400U-P1	400	17.65
KA600U-P1	600	26.00



L Style Brackets

0338



£

KA201-P1	200	14.10
KA301-P1	300	15.10
KA401-P1	400	15.10
KA601-P1	600	23.30

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE