



## Air Preparation Equipment



### Filter + Regulator + Lubricator

**Element:**  
20 Micron (5 micron & coalescent available).

**Regulation:**  
Standard is relieving, non-relieving available.

Standard Regulation is 0-8 bar (0-2, 0-4 & 0-12 also available).

**Note:** 1/4" BSP units do not come with bowl guard as standard, please see accessories listing for guards.



Fully Assembled Combination with 0-10 bar Pressure Gauge & Mounting Bracket, BSPP

KELM™ Pneumatics	0020			
Pneumatic & Vacuum Equipment	2020-2610	1/4"	Semi Auto	83.30
	2020-2628	3/8"	Semi Auto	102.30
	2020-2636	1/2"	Semi Auto	142.75
Valves	2020-2644	3/4"	Semi Auto	210.10

### Micro-regulators

This model is equipped with an internal uni-directional valve which allows quick exhaust of pressure during depressurization of the circuit. Exhaust phase of the valve will not suffer load losses thanks to its passing through the unidirectional valve, thus guaranteeing speed and high performance. Product complies with Directive 2002/95/CE (RoHS).

**Maximum Ambient Temperature:**  
50°C

**Pressure Range:**  
0-2 bar, 0-4 bar, 0-8 bar, 0-12.5 bar  
0-0.1 bar, 0-0.2 MPa, 0-0.4 MPa, 0-0.8 MPa, 0-1.25 MPa.

Tech Sheet 10468



Quick Exhaust SRU, 1/8" BSPP

0020		
038.00.00441	0-2	67.05
038.00.00442	0-4	64.60
038.00.00443	0-8	67.05
038.00.00444	0-12	67.05

### Filter Regulator + Lubricator

**Element:**  
20 Micron (5 micron & coalescent available).

**Regulation:**  
Standard is relieving, non-relieving available. Standard Regulation is 0-8 bar (0-2, 0-4 & 0-12 springs also available).

**Note:** 1/4" BSP units do not come with bowl guard as standard, please see accessories listing for guards.

**N.B.** 1/4" not supplied with Protective Bowls.



Fully Assembled Combination with 0-10 bar Pressure Gauge & Mounting Bracket, BSPP

0020			
2020-2461	1/4"	Semi Auto	88.95
2019-4114	3/8"	Semi Auto	96.85
2020-2495	1/2"	Semi Auto	155.60
2020-2511	3/4"	Semi Auto	150.05
2020-2537	1"	Semi Auto	292.10

### Regulator

**Regulation:**  
Standard is relieving, non-relieving available.

Standard Regulation is 0-8 bar (0-2, 0-4 & 0-12 also available).



Fully Assembled with 0-10 bar Pressure Gauge & Mounting Bracket, BSPP

0020		
2020-2651	1/8"	31.50
2020-2669	1/4"	34.60
2020-2677	3/8"	61.20
2020-2685	1/2"	71.05
2020-2693	3/4"	108.75

Designed for food sector applications, especially suggested for water pressure regulation.

**Fluid:** Air or water  
Balanced valve  
No relieving function  
Two ways body featuring inlet and outlet ports only, to avoid leakage from unused connections.

**Max Fluid Temperature:** (cold drinking water) 23°C

**Max Torque Inserts:** 1/8" IN-OUT 20 Nm

**Weight:** 0.100 Kg

Tech Sheet 10469



Stainless Steel INOX, 1/8" BSPP

0020		
039.00.00227	0-2	178.70
039.00.00228	0-4	178.70
039.00.00229	0-8	178.70
039.00.00230	0-12	178.70



## For Direct Drive & Belt Driven Compressors

see pages 1444-1447

