



# Glycerine Gauges & Accessories



## All Stainless Steel Gauges, 1/4" Bottom Connection



1/4" BSPP

| 0021        | mm | PSI    | bar   | £     |
|-------------|----|--------|-------|-------|
| SSG63-001BG | 63 | 0-15   | 0-1   | 66.95 |
| SSG63-004BG | 63 | 0-60   | 0-4   | 66.95 |
| SSG63-012BG | 63 | 0-200  | 0-12  | 66.95 |
| SSG63-025BG | 63 | 0-400  | 0-25  | 66.95 |
| SSG63-060BG | 63 | 0-1000 | 0-60  | 66.95 |
| SSG63-200BG | 63 | 0-3000 | 0-200 | 66.95 |
| SSG63-400BG | 63 | 0-6000 | 0-400 | 66.95 |

## All Stainless Steel Gauges, 1/2" Bottom Connection



1/2" BSPP

| 0021         | mm  | PSI    | bar   | £      |
|--------------|-----|--------|-------|--------|
| SHG100-002BG | 100 | 0-30   | 0-2   | 228.20 |
| SHG100-006BG | 100 | 0-100  | 0-6   | 228.20 |
| SHG100-016BG | 100 | 0-250  | 0-16  | 228.20 |
| SHG100-040BG | 100 | 0-600  | 0-40  | 228.20 |
| SHG100-100BG | 100 | 0-1500 | 0-100 | 228.20 |
| SHG100-250BG | 100 | 0-4000 | 0-250 | 228.20 |
| SHG100-600BG | 100 | 0-9000 | 0-600 | 228.20 |

## All Stainless Steel Gauges, 1/4" Centre Back Connection



1/4" BSPP

| 0021      | mm | PSI    | bar   | £     |
|-----------|----|--------|-------|-------|
| 2038-8583 | 40 | 0-200  | 0-12  | 50.45 |
| 2038-8591 | 40 | 0-300  | 0-20  | 50.45 |
| 2038-8609 | 40 | 0-600  | 0-40  | 50.45 |
| 2038-8625 | 40 | 0-900  | 0-60  | 50.45 |
| 2038-8633 | 40 | 0-4000 | 0-250 | 50.45 |
| 2038-8534 | 63 | 0-200  | 0-12  | 73.40 |
| 2038-8567 | 63 | 0-900  | 0-60  | 73.40 |
| 2038-8575 | 63 | 0-4000 | 0-250 | 73.40 |

## All Stainless Steel Gauges, 1/2" Centre Back Connection



1/2" BSPP

| 0021      | mm  | PSI    | bar   | £      |
|-----------|-----|--------|-------|--------|
| 2038-8435 | 100 | 0-200  | 0-12  | 198.90 |
| 2038-8443 | 100 | 0-300  | 0-20  | 198.90 |
| 2038-8450 | 100 | 0-600  | 0-40  | 198.90 |
| 2038-8476 | 100 | 0-4000 | 0-250 | 198.90 |

## Back Rubber Gauge Protectors



Open



Closed

| 0021   | Open   | £     |
|--------|--------|-------|
| G63-OB | Open   | 26.90 |
| G63-CB | Closed | 26.90 |

## Gauge Snubbers



Working Pressure:  
20-300 bar

Tech Sheet  
28



High Pressure

| 0021  | Male | Female | £     |
|-------|------|--------|-------|
| 130.4 | 1/4" | 1/4"   | 30.40 |
| 130.3 | 3/8" | 3/8"   | 33.95 |
| 130.2 | 1/2" | 1/2"   | 45.30 |

Gauge Snubbers are a great way of protecting gauges from damage, with sudden impact pressure i.e. when full line pressure is introduced to the gauge damage can occur. With the use of the snubber the gauge will be protected.



Working Pressure:  
0-20 bar



Low Pressure

| 0021  | Male | Female | £     |
|-------|------|--------|-------|
| 131.8 | 1/8" | 1/8"   | 12.10 |
| 131.4 | 1/4" | 1/4"   | 12.15 |
| 131.3 | 3/8" | 3/8"   | 16.80 |
| 131.2 | 1/2" | 1/2"   | 20.85 |

## Bleeder Valve



Temperature Range:  
-20°C to +85°C



Pressure Rating:  
10 bar



BSPP

| 0021  | £          |
|-------|------------|
| 124.8 | 1/8" 10.90 |
| 124.4 | 1/4" 10.90 |
| 124.3 | 3/8" 11.65 |

All Pressure Gauges can be supplied with a Calibration Certificate at a nominal charge. Please call our Business Development Team for Price & Delivery.