



Air Preparation



Page Tech Sheet **3063**



Temperature Rate:
-5°C to +60°C

Maximum Pressure:
10 bar

40 Micron fitted as standard
Auto or Semi-Auto Drain fitted as standard
Guarded Bowl Protection on Series 300 & 400


200 Series Filters



Semi-Auto Drains, supplied with Mounting Bracket, BSPP

0338			£
KFS200-06	1/8"	3000	30.95
KFS200-08	1/4"	3000	30.95

300 Series Filters



Auto Drain, supplied with Mounting Bracket, BSPP

0338			£
KFS300-08-A	1/4"	5000	61.40
KFS300-10-A	3/8"	5000	61.40
KFS300-15-A	1/2"	5000	61.40

Semi-Auto Drains, supplied with Mounting Bracket, BSPP

0338			£
KFS300-08	1/4"	5000	50.15
KFS300-10	3/8"	5000	50.15
KFS300-15	1/2"	5000	50.15

400 Series Filters



Auto Drain, supplied with Mounting Bracket, BSPP

0338			£
KFS400-10-A	3/8"	7500	103.15
KFS400-15-A	1/2"	7500	103.15

Semi-Auto Drains, supplied with Mounting Bracket, BSPP

0338			£
KFS400-10	3/8"	7500	76.60
KFS400-15	1/2"	7500	76.60

600 Series Filters



Auto Drain, supplied with Mounting Bracket, BSPP

0338			£
KFS600-20-A	3/4"	10000	213.40
KFS600-25-A	1"	10000	213.40

Semi-Auto Drains, supplied with Mounting Bracket, BSPP

0338			£
KFS600-20	3/4"	10000	172.30
KFS600-25	1"	10000	172.30

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE