



## Air Preparation



**Working Temperature:**  
-20°C to +70°C

**Maximum Working Pressure:**  
9 bar

Can be fitted to any combination units, fitted before the lubricator it can be used to port off a non-lubricated air supply that might be required for your system. These units are to be used in conjunction with Kelm™ Air Preparation, or as a stand alone BSPP manifold block. When using with existing Kelm™ Air Preparation, you will also require additional fixing brackets.

### 200 Series Porting Blocks



BSPP

0338



£

KA200-06  
KA200-08

1/8"  
1/4"

24.10  
24.10

### 400 Series Porting Blocks



BSPP

0338



£

KA400-10  
KA400-15

3/8"  
1/2"

32.75  
32.75

### 300 Series Porting Blocks



BSPP

0338



£

KA300-08  
KA300-10

1/4"  
3/8"

27.10  
27.10

### 600 Series Porting Blocks



BSPP

0338



£

KA600-20  
KA600-25

3/4"  
1"

87.35  
87.35

### Fixing Brackets



U Style Brackets

0338

To Suit Unit

£

KA200U-P1  
KA300U-P1  
KA400U-P1  
KA600U-P1

200  
300  
400  
600

13.50  
14.60  
17.65  
26.00



L Style Brackets

0338

To Suit Unit

£

KA201-P1  
KA301-P1  
KA401-P1  
KA601-P1

200  
300  
400  
600

14.10  
15.10  
15.10  
23.30

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE