



Pneumatic Cylinders



Page Tech Sheet 3001

ISO6432 Mini Cylinders



Working Temperature:
-20°C to +70°C



Operating Pressure:
1 to 10 bar



Medium:

Clean Compressed Air. Filtered (40µm) & Lubricated Cushioning KA-Bumper, KB-Adjustable

Full technical specifications available on request

N.B. Bore sizes 32mm-40mm are available on a lead time. Please contact our sales office for details.

• STAINLESS STEEL PISTON ROD & BARREL AS STANDARD.



Magnetic Double Acting

0334	mm	mm	mm	Locknut	Rod Thread	£
KA-8X10-S-CA	8	10	M5	M12 x 1.25	M4 x 0.7	30.90
KA-8X15-S-CA	8	15	M5	M12 x 1.25	M4 x 0.7	30.90
KA-8X20-S-CA	8	20	M5	M12 x 1.25	M4 x 0.7	30.90
KA-8X25-S-CA	8	25	M5	M12 x 1.25	M4 x 0.7	30.90
KA-8X30-S-CA	8	30	M5	M12 x 1.25	M4 x 0.7	32.15
KA-8X40-S-CA	8	40	M5	M12 x 1.25	M4 x 0.7	32.15
KA-8X50-S-CA	8	50	M5	M12 x 1.25	M4 x 0.7	32.15
KA-8X60-S-CA	8	60	M5	M12 x 1.25	M4 x 0.7	33.35
KA-8X75-S-CA	8	75	M5	M12 x 1.25	M4 x 0.7	33.35
KA-8X80-S-CA	8	80	M5	M12 x 1.25	M4 x 0.7	34.95
KA-8X100-S-CA	8	100	M5	M12 x 1.25	M4 x 0.7	34.95
KA-8X125-S-CA	8	125	M5	M12 x 1.25	M4 x 0.7	36.50
KA-8X150-S-CA	8	150	M5	M12 x 1.25	M4 x 0.7	38.10
KA-10X10-S-CA	10	10	M5	M12 x 1.25	M4 x 0.7	32.15
KA-10X15-S-CA	10	15	M5	M12 x 1.25	M4 x 0.7	32.15
KA-10X20-S-CA	10	20	M5	M12 x 1.25	M4 x 0.7	32.15
KA-10X25-S-CA	10	25	M5	M12 x 1.25	M4 x 0.7	32.15
KA-10X30-S-CA	10	30	M5	M12 x 1.25	M4 x 0.7	34.05
KA-10X40-S-CA	10	40	M5	M12 x 1.25	M4 x 0.7	34.05
KA-10X50-S-CA	10	50	M5	M12 x 1.25	M4 x 0.7	34.05
KA-10X60-S-CA	10	60	M5	M12 x 1.25	M4 x 0.7	35.90
KA-10X75-S-CA	10	75	M5	M12 x 1.25	M4 x 0.7	35.90
KA-10X80-S-CA	10	80	M5	M12 x 1.25	M4 x 0.7	38.10
KA-10X100-S-CA	10	100	M5	M12 x 1.25	M4 x 0.7	38.10
KA-10X125-S-CA	10	125	M5	M12 x 1.25	M4 x 0.7	39.85
KA-10X150-S-CA	10	150	M5	M12 x 1.25	M4 x 0.7	40.40
KA-10X160-S-CA	10	160	M5	M12 x 1.25	M4 x 0.7	41.00
KA-10X175-S-CA	10	175	M5	M12 x 1.25	M4 x 0.7	41.65
KA-10X200-S-CA	10	200	M5	M12 x 1.25	M4 x 0.7	42.20
KA-12X10-S-CA	12	10	M5	M16 x 1.5	M6 x 1.0	36.30
KA-12X15-S-CA	12	15	M5	M16 x 1.5	M6 x 1.0	36.30
KA-12X20-S-CA	12	20	M5	M16 x 1.5	M6 x 1.0	36.30
KA-12X25-S-CA	12	25	M5	M16 x 1.5	M6 x 1.0	37.35
KA-12X30-S-CA	12	30	M5	M16 x 1.5	M6 x 1.0	39.25
KA-12X40-S-CA	12	40	M5	M16 x 1.5	M6 x 1.0	39.25
KA-12X50-S-CA	12	50	M5	M16 x 1.5	M6 x 1.0	39.25
KA-12X60-S-CA	12	60	M5	M16 x 1.5	M6 x 1.0	40.60
KA-12X75-S-CA	12	75	M5	M16 x 1.5	M6 x 1.0	40.60
KA-12X80-S-CA	12	80	M5	M16 x 1.5	M6 x 1.0	41.30
KA-12X100-S-CA	12	100	M5	M16 x 1.5	M6 x 1.0	42.75
KA-12X125-S-CA	12	125	M5	M16 x 1.5	M6 x 1.0	44.30
KA-12X150-S-CA	12	150	M5	M16 x 1.5	M6 x 1.0	38.90
KA-12X160-S-CA	12	160	M5	M16 x 1.5	M6 x 1.0	40.75
KA-12X175-S-CA	12	175	M5	M16 x 1.5	M6 x 1.0	40.75
KA-12X200-S-CA	12	200	M5	M16 x 1.5	M6 x 1.0	42.50
KA-12X250-S-CA	12	250	M5	M16 x 1.5	M6 x 1.0	46.45
KB-16X10-S-CA	16	10	M5	M16 x 1.5	M6 x 1.0	48.70
KB-16X15-S-CA	16	15	M5	M16 x 1.5	M6 x 1.0	48.70
KB-16X20-S-CA	16	20	M5	M16 x 1.5	M6 x 1.0	48.70
KB-16X25-S-CA	16	25	M5	M16 x 1.5	M6 x 1.0	48.70

0334	mm	mm	mm	Locknut	Rod Thread	£
KB-16X30-S-CA	16	30	M5	M16 x 1.5	M6 x 1.0	50.90
KB-16X40-S-CA	16	40	M5	M16 x 1.5	M6 x 1.0	50.90
KB-16X50-S-CA	16	50	M5	M16 x 1.5	M6 x 1.0	50.90
KB-16X60-S-CA	16	60	M5	M16 x 1.5	M6 x 1.0	52.90
KB-16X75-S-CA	16	75	M5	M16 x 1.5	M6 x 1.0	52.90
KB-16X80-S-CA	16	80	M5	M16 x 1.5	M6 x 1.0	55.00
KB-16X100-S-CA	16	100	M5	M16 x 1.5	M6 x 1.0	55.00
KB-16X125-S-CA	16	125	M5	M16 x 1.5	M6 x 1.0	56.95
KB-16X150-S-CA	16	150	M5	M16 x 1.5	M6 x 1.0	59.15
KB-16X160-S-CA	16	160	M5	M16 x 1.5	M6 x 1.0	61.20
KB-16X175-S-CA	16	175	M5	M16 x 1.5	M6 x 1.0	61.20
KB-16X200-S-CA	16	200	M5	M16 x 1.5	M6 x 1.0	63.15
KB-16X250-S-CA	16	250	M5	M16 x 1.5	M6 x 1.0	67.35
KB-16X300-S-CA	16	300	M5	M16 x 1.5	M6 x 1.0	71.90
KB-20X10-S-CA	20	10	1/8"	M22 x 1.5	M8 x 1.25	46.05
KB-20X15-S-CA	20	15	1/8"	M22 x 1.5	M8 x 1.25	46.05
KB-20X20-S-CA	20	20	1/8"	M22 x 1.5	M8 x 1.25	46.05
KB-20X25-S-CA	20	25	1/8"	M22 x 1.5	M8 x 1.25	46.70
KB-20X30-S-CA	20	30	1/8"	M22 x 1.5	M8 x 1.25	51.30
KB-20X40-S-CA	20	40	1/8"	M22 x 1.5	M8 x 1.25	51.30
KB-20X50-S-CA	20	50	1/8"	M22 x 1.5	M8 x 1.25	51.30
KB-20X60-S-CA	20	60	1/8"	M22 x 1.5	M8 x 1.25	55.45
KB-20X75-S-CA	20	75	1/8"	M22 x 1.5	M8 x 1.25	55.45
KB-20X80-S-CA	20	80	1/8"	M22 x 1.5	M8 x 1.25	55.45
KB-20X100-S-CA	20	100	1/8"	M22 x 1.5	M8 x 1.25	56.10
KB-20X125-S-CA	20	125	1/8"	M22 x 1.5	M8 x 1.25	56.50
KB-20X150-S-CA	20	150	1/8"	M22 x 1.5	M8 x 1.25	56.50
KB-20X160-S-CA	20	160	1/8"	M22 x 1.5	M8 x 1.25	59.10
KB-20X175-S-CA	20	175	1/8"	M22 x 1.5	M8 x 1.25	59.75
KB-20X200-S-CA	20	200	1/8"	M22 x 1.5	M8 x 1.25	60.35
KB-20X250-S-CA	20	250	1/8"	M22 x 1.5	M8 x 1.25	64.60
KB-20X300-S-CA	20	300	1/8"	M22 x 1.5	M8 x 1.25	65.80
KB-20X350-S-CA	20	350	1/8"	M22 x 1.5	M8 x 1.25	68.60
KB-20X400-S-CA	20	400	1/8"	M22 x 1.5	M8 x 1.25	77.75
KB-20X450-S-CA	20	450	1/8"	M22 x 1.5	M8 x 1.25	82.80
KB-20X500-S-CA	20	500	1/8"	M22 x 1.5	M8 x 1.25	84.50
KB-25X10-S-CA	25	10	1/8"	M22 x 1.5	M10 x 1.25	48.25
KB-25X15-S-CA	25	15	1/8"	M22 x 1.5	M10 x 1.25	48.85
KB-25X20-S-CA	25	20	1/8"	M22 x 1.5	M10 x 1.25	49.50
KB-25X25-S-CA	25	25	1/8"	M22 x 1.5	M10 x 1.25	50.05
KB-25X30-S-CA	25	30	1/8"	M22 x 1.5	M10 x 1.25	50.90
KB-25X40-S-CA	25	40	1/8"	M22 x 1.5	M10 x 1.25	50.90
KB-25X50-S-CA	25	50	1/8"	M22 x 1.5	M10 x 1.25	51.30
KB-25X60-S-CA	25	60	1/8"	M22 x 1.5	M10 x 1.25	51.30
KB-25X75-S-CA	25	75	1/8"	M22 x 1.5	M10 x 1.25	51.90
KB-25X80-S-CA	25	80	1/8"	M22 x 1.5	M10 x 1.25	51.90
KB-25X100-S-CA	25	100	1/8"	M22 x 1.5	M10 x 1.25	52.40
KB-25X125-S-CA	25	125	1/8"	M22 x 1.5	M10 x 1.25	54.90
KB-25X150-S-CA	25	150	1/8"	M22 x 1.5	M10 x 1.25	56.10
KB-25X160-S-CA	25	160	1/8"	M22 x 1.5	M10 x 1.25	57.70

Further sizes in this range continued on next page

- Hydraulics
- Hydraulic QRC
- Pneumatic QRC
- Ind. Air Prep, Monitor & Test
- KELMK™ Pneumatics
- Pneumatic & Vacuum Equipment
- Valves
- Ring Main Systems
- Adaptors & Fittings
- Stainless Steel
- Malleable Iron
- Hose, Tubing & Couplings
- Clamps & Clips
- Sprays & Adhesives
- Blow Guns & Vacuum
- Wash Down & Fuelling
- Air Tools
- Tools, Hardware & PPE