



Pilot Valves



Operational Temperature:
-20°C to +70°C


Working Pressure:
1.5 to 8 bar

Medium: Clean Compressed Air.
Filtered (40µm) & Lubricated
Material: Body: Aluminium Alloy **Seals:** NBR

Section 5 – KELMK™ Pneumatics

Pilot 3/2 Way Valves


Tech Sheet
3036



Pilot/Spring, Normally Open, BSPP

0335		£
CKA210-06-NO	1/8"	72.75
CKA210-08-NO	1/4"	72.75
CKA310-10-NO	3/8"	133.60

Tech Sheet
3036



Pilot/Spring, Normally Closed, BSPP

0335		£
CKA210-06-NC	1/8"	72.75
CKA210-08-NC	1/4"	72.75
CKA310-10-NC	3/8"	133.60

Tech Sheet
3036



Pilot/Pilot, BSPP

0335		£
CKA220-06	1/8"	92.35
CKA220-08	1/4"	92.35
CKA320-10	3/8"	133.50

Pilot 5/2 Way Valves

Tech Sheet
3037



Pilot/Spring, BSPP

0335		£
DKA210-06	1/8"	72.75
DKA210-08	1/4"	72.75
DKA310-10	3/8"	103.80
DKA410-15	1/2"	109.20

Tech Sheet
3037



Pilot/Pilot, BSPP

0335		£
DKA220-06	1/8"	95.30
DKA220-08	1/4"	95.30
DKA320-10	3/8"	109.20
DKA420-15	1/2"	115.25