



Solenoid Valves



Operational Temperature:
-20°C to +70°C

Working Pressure:
1.5 to 8 bar

Medium: Clean Compressed Air. Filtered (40µm) & Lubricated
Material: Body: Aluminium Alloy **Seals:** NBR
Full technical specifications available on request

Solenoid 5/2 Way Valves



Solenoid/Spring, BSPP

0335		£
DKV210-06	1/8"	63.45
DKV210-08	1/4"	66.75
DKV310-10	3/8"	90.50
DKV410-15	1/2"	105.40



Solenoid/Solenoid, BSPP

0335		£
DKV220-06	1/8"	87.15
DKV220-08	1/4"	94.80
DKV320-10	3/8"	114.20
DKV420-15	1/2"	210.65



Operational Temperature:
-20°C to +70°C

Working Pressure:
1.5 to 8 bar

Please contact our Technical Department if larger manifolds are required up to 16 stations.

Solenoid 5/3 Way Valves



Solenoid/Solenoid, Fully Sealed Mid Position, BSPP

0335		£
DKV230C-06	1/8"	114.50
DKV230C-08	1/4"	125.90
DKV330C-10	3/8"	145.45
DKV430C-15	1/2"	274.20



Solenoid/Solenoid, Centre Open Pressurised, BSPP

0335		£
DKV230P-06	1/8"	114.50
DKV230P-08	1/4"	125.90
DKV330P-10	3/8"	145.45
DKV430P-15	1/2"	160.15



Solenoid/Solenoid, Supply Sealed Mid Position, BSPP

0335		£
DKV230E-06	1/8"	114.50
DKV230E-08	1/4"	125.90
DKV330E-10	3/8"	145.45
DKV430E-15	1/2"	160.15

For Solenoid Coils to suit Valves see page 508



Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE