



## One Touch All Metal Push-in Fittings



### Page Tech Sheet 3130

**Temperature Range:**  
-10°C to +60°C  
(dependant upon tubing specification)

**Pressure:**  
0.8-8 bar (dependent upon tubing specification)

Tube connection and disconnection can be repeated several times and is performed with one hand, without the use of tools. Nickel-plated brass bodies ensures anti-corrosion and anti-contamination.

**Material:** Body & Collet: Nickel plated brass  
**O-Ring:** NBR  
**Threads:** BSPT, BSPP & Metric  
**Tube to Connect:** PU, PE, Nylon 6-11-12  
**Fluid:** Compressed air

### Male Centre Legs, Swivel Tees



Male Thread, BSPP

0315	OD mm		£
MPB6-G01	6	1/8"	6.10
MPB6-G02	6	1/4"	6.10
MPB8-G01	8	1/8"	7.05
MPB8-G02	8	1/4"	7.10
MPB10-G02	10	1/4"	8.60
MPB10-G03	10	3/8"	8.35
MPB12-G03	12	3/8"	9.50
MPB12-G04	12	1/2"	9.60

### Male Run Leg, Swivel Tees



Male Thread, Metric & BSPP

0315	OD mm		£
MPD4-M5	4	M5	5.35
MPD4-G01	4	1/8"	5.65
MPD4-G02	4	1/4"	5.75
MPD6-G01	6	1/8"	7.10
MPD6-G02	6	1/4"	7.20
MPD8-G01	8	1/8"	8.25
MPD8-G02	8	1/4"	8.35
MPD8-G03	8	3/8"	8.40
MPD10-G02	10	1/4"	10.10
MPD10-G03	10	3/8"	10.20
MPD10-G04	10	1/2"	10.45
MPD12-G02	12	1/4"	10.95
MPD12-G03	12	3/8"	11.10
MPD12-G04	12	1/2"	11.30

### Male Stud Swivel Ys



Male Thread, BSPP

0315	OD mm		£
MPWT4-G01	4	1/8"	5.65
MPWT4-G02	4	1/4"	5.65
MPWT6-G01	6	1/8"	6.45
MPWT6-G02	6	1/4"	7.25
MPWT8-G01	8	1/8"	8.25
MPWT8-G02	8	1/4"	8.35
MPWT8-G03	8	3/8"	8.40
MPWT10-G02	10	1/4"	10.10
MPWT10-G03	10	3/8"	10.20
MPWT10-G04	10	1/2"	11.50
MPWT12-G02	12	1/4"	12.05
MPWT12-G03	12	3/8"	12.15
MPWT12-G04	12	1/2"	13.70

### Male Single Banjo



Male Thread, Metric & BSPP

0315	OD mm		£
MPH4-M5	4	M5	3.65
MPH4-G01	4	1/8"	5.35
MPH4-G02	4	1/4"	5.50
MPH4-M6	4	M6	4.70
MPH6-M5	6	M5	4.50
MPH6-G01	6	1/8"	5.65
MPH6-M6	6	M6	4.75
MPH6-G02	6	1/4"	6.20
MPH8-G01	8	1/8"	6.30
MPH8-G02	8	1/4"	7.05
MPH8-G03	8	3/8"	6.95
MPH10-G02	10	1/4"	8.35
MPH10-G03	10	3/8"	8.95
MPH10-G04	10	1/2"	9.90
MPH12-G02	12	1/4"	9.05
MPH12-G03	12	3/8"	9.85
MPH12-G04	12	1/2"	10.65

### Stacking Single Banjo



Female Thread, BSPP

0315	OD mm		£
MPHF04-G01	4	1/8"	5.50
MPHF04-G02	4	1/4"	6.80
MPHF05-G01	5	1/8"	6.10
MPHF05-G02	5	1/4"	6.80
MPHF06-G01	6	1/8"	6.10
MPHF06-G02	6	1/4"	7.05
MPHF08-G01	8	1/8"	7.10
MPHF08-G02	8	1/4"	7.50
MPHF08-G03	8	3/8"	7.70
MPHF08-G04	8	1/2"	9.30
MPHF10-G01	10	1/8"	8.70
MPHF10-G02	10	1/4"	8.35
MPHF10-G03	10	3/8"	8.70
MPHF10-G04	10	1/2"	10.10
MPHF12-G01	12	1/8"	10.45
MPHF12-G02	12	1/4"	10.45
MPHF12-G03	12	3/8"	10.60
MPHF12-G04	12	1/2"	10.60
MPHF14-G03	14	3/8"	17.60
MPHF14-G04	14	1/2"	17.60
MPHF16-G03	16	3/8"	20.20
MPHF16-G04	16	1/2"	20.20

### Speed Control Valves

Tube x Metric & BSPT

0315	OD mm		£
MNSE6-M5	6	M5	13.80
MNSE6-G01	6	1/8"	13.95
MNSE6-M6	6	M6	15.25
MNSE6-G02	6	1/4"	14.00
MNSE8-G01	8	1/8"	15.00
MNSE8-G02	8	1/4"	15.05

Tube x Metric & BSPP

0315	OD mm		£
MNSE4-M5	4	M5	13.70
MNSE4-G01	4	1/8"	13.70
MNSE4-G02	4	1/4"	15.05
MNSE6-G01	6	1/8"	16.25
MNSE6-G02	6	1/4"	17.75
MNSE8-G01	8	1/8"	11.30
MNSE8-G02	8	1/4"	18.00
MNSE8-G03	8	3/8"	18.55
MNSE10-G02	10	1/4"	18.00
MNSE10-G03	10	3/8"	19.00
MNSE10-G04	10	1/2"	20.60
MNSE12-G02	12	1/4"	18.40
MNSE12-G03	12	3/8"	19.50
MNSE12-G04	12	1/2"	21.25

Tube x BSPP with Slotted Head

0315	OD mm		£
MNSP4-G01	4	1/8"	13.85
MNSP4-G02	4	1/4"	14.50
MNSP6-G01	6	1/8"	15.80
MNSP6-G02	6	1/4"	16.15
MNSP8-G01	8	1/8"	17.40
MNSP8-G02	8	1/4"	17.90
MNSP8-G03	8	3/8"	18.70
MNSP8-G04	8	1/2"	20.30
MNSP10-G02	10	1/4"	18.00
MNSP10-G03	10	3/8"	18.85
MNSP10-G04	10	1/2"	20.45
MNSP12-G02	12	1/4"	18.30
MNSP12-G03	12	3/8"	19.15
MNSP12-G04	12	1/2"	21.05

- Hydraulics
- Hydraulic QRC
- Pneumatic QRC
- Ind. Air Prep, Monitor & Test
- KELM™ Pneumatics
- Pneumatic & Vacuum Equipment
- Valves
- Ring Main Systems
- Adaptors & Fittings
- Stainless Steel
- Malleable Iron
- Hose, Tubing & Couplings
- Clamps & Clips
- Sprays & Adhesives
- Blow Guns & Vacuum
- Wash Down & Fuelling
- Air Tools
- Tools, Hardware & PPE