



## One Touch All Metal Push-in Fittings



**Temperature Range:**  
-10°C to +60°C  
(dependant upon tubing specification)

**Pressure:**  
0.8-8 bar (dependent upon tubing specification)

Tube connection and disconnection can be repeated several times and is performed with one hand, without the use of tools. Nickel-plated brass bodies ensures anti-corrosion and anti-contamination.

**Material:** Body & Collet: Nickel plated brass  
**O-Ring:** NBR  
**Threads:** BSPT, BSPP & Metric  
**Tube to Connect:** PU, PE, Nylon 6-11-12  
**Fluid:** Compressed air

### Tube x Tube Connectors



Equal Straights

0315	OD mm	£
MPUC-4	4	3.40
MPUC-6	6	3.60
MPUC-8	8	3.95
MPUC-10	10	4.80
MPUC-12	12	5.45



Equal Ys

0315	OD mm	£
MPY-6	6	5.30
MPY-8	8	6.80



Unequal Straights

0315	OD mm	OD mm	£
MPG6-4	6	4	4.40
MPG8-6	8	6	4.85
MPG10-8	10	8	5.85
MPG12-10	12	10	6.65



Equal Bulkheads

0315	OD mm	£
MPM-4	4	4.00
MPM-6	6	4.80
MPM-8	8	5.30
MPM-10	10	6.20
MPM-12	12	7.80

### Tube x Stem Connectors



Straight, Tube x Stem

0315	Stem OD mm	OD mm	£
MPJG6-4	6	4	3.45
MPJG8-4	8	4	3.60
MPJG8-6	8	6	3.75
MPJG10-6	10	6	3.90
MPJG10-8	10	8	4.00
MPJG12-8	12	8	4.25
MPJG12-10	12	10	4.80



Equal Elbows

0315	OD mm	£
MPUL-4	4	3.65
MPUL-6	6	4.80
MPUL-8	8	5.15
MPUL-10	10	5.75
MPUL-12	12	7.25



Equal Tees

0315	OD mm	£
MPUT-4	4	4.80
MPUT-6	6	5.30
MPUT-8	8	6.80
MPUT-10	10	8.35
MPUT-12	12	9.30

### Standpipes



Male Thread, BSPP

0315	Stem OD mm	Thread	£
MPCJ4-G01	4	1/8"	2.25
MPCJ4-G02	4	1/4"	2.70
MPCJ6-G01	6	1/8"	2.35
MPCJ6-G02	6	1/4"	2.80
MPCJ8-G02	8	1/4"	2.90
MPCJ8-G03	8	3/8"	3.60
MPCJ8-G04	8	1/2"	4.90
MPCJ10-G02	10	1/4"	3.10
MPCJ10-G03	10	3/8"	3.85
MPCJ10-G04	10	1/2"	5.15
MPCJ12-G02	12	1/4"	3.40
MPCJ12-G03	12	3/8"	3.90
MPCJ12-G04	12	1/2"	5.15



Female Thread, BSPP

0315	Stem OD mm	Thread	£
MPCFJ4-G01	4	1/8"	1.80
MPCFJ4-G02	4	1/4"	2.35
MPCFJ6-G01	6	1/8"	1.95
MPCFJ6-G02	6	1/4"	2.60
MPCFJ8-G02	8	1/4"	2.80
MPCFJ8-G03	8	3/8"	3.85
MPCFJ8-G04	8	1/2"	5.50
MPCFJ10-G02	10	1/4"	2.95
MPCFJ10-G03	10	3/8"	4.15
MPCFJ10-G04	10	1/2"	5.90
MPCFJ12-G02	12	1/4"	3.30
MPCFJ12-G03	12	3/8"	4.40
MPCFJ12-G04	12	1/2"	6.20

### Shut-off Valves



Tube x Tube

0315	OD mm	£
MNSF04	4	22.70
MNSF06	6	24.00
MNSF08	8	25.25
MNSF10	10	26.45
MNSF12	12	29.00