



Micro One Touch NPT & UNF Plastic Push-in Fittings



Page Tech Sheet **10001**

Working Temperature:
-0°C to +60°C

Maximum Working Pressure:
10 bar (150 psi)

40% less volume & a 20% smaller OD than the standard One Touch Design

Micro One Touch fittings are specially designed for pneumatic systems that are use in confined spaces, saving you time & money on installations.

Bulkheads



Equal Straight

0315	OD	1-9 £	10+ £
PMM1/8C	1/8"	12.35	9.90
PMM5/32C	5/32"	12.35	9.90
PMM1/4C	1/4"	12.35	9.90

Speed Control Valves



Male Thread, UNF

0315	OD	Thread	1-9 £	10+ £
NSE1/8-U10C	1/8"	10-32	15.45	12.35
NSE5/32-U10C	5/32"	10-32	15.45	12.35
NSE1/4-U10C	1/4"	10-32	15.45	12.35

Equal Elbow



0315	OD	1-9 £	10+ £
PLM1/8C	1/8"	12.35	9.90
PLM5/32C	5/32"	12.35	9.90
PLM1/4C	1/4"	12.35	9.90



For **KELM™**
Logic Valves
see page 516

Section 5 – KELM™ Pneumatics

- Hydraulics
- Hydraulic QRC
- Pneumatic QRC
- Ind. Air Prep., Monitor & Test
- KELM™ Pneumatics**
- Pneumatic & Vacuum Equipment
- Valves
- Ring Main Systems
- Adaptors & Fittings
- Stainless Steel
- Malleable Iron
- Hose, Tubing & Couplings
- Clamps & Clips
- Sprays & Adhesives
- Blow Guns & Vacuum
- Wash Down & Fuelling
- Air Tools
- Tools, Hardware & PPE