

# One Touch All Stainless Steel Push-in Fittings



## Page Tech Sheet 10257

**Working Temperature:**  
-20°C to +200°C

**Maximum Working Pressure:**  
10 bar  
**Negative Pressure:**  
750mm Hg (10Torr)

**Material:**  
**Body & Collet:** 316 Stainless Steel  
**O-Ring:** FKM

**Tube to Connect:** PU, Nylon & Teflon  
**Media:** Compressed Air, Steam Water & Other Compatible Liquids

### Tube x Tube Connectors



#### Equal Straights

0386	OD mm	£
SSPUC-4	4	21.65
SSPUC-6	6	22.90
SSPUC-8	8	26.45
SSPUC-10	10	29.40
SSPUC-12	12	35.25



#### Unequal Straights

0386	OD mm	OD mm	£
SSPG6-4	6	4	24.10
SSPG8-4	8	4	28.20
SSPG8-6	8	6	28.20
SSPG10-6	10	6	31.15
SSPG10-8	10	8	31.15
SSPG12-8	12	8	37.00
SSPG12-10	12	10	37.00



#### Equal Elbows

0386	OD mm	£
SSPUL-4	4	27.95
SSPUL-6	6	30.00
SSPUL-8	8	31.75
SSPUL-10	10	35.85
SSPUL-12	12	42.35



#### Equal Tees

0386	OD mm	£
SSPUT-4	4	38.75
SSPUT-6	6	40.55
SSPUT-8	8	45.85
SSPUT-10	10	54.10
SSPUT-12	12	64.65



#### Equal Bulkheads

0386	OD mm	£
SSPM-4	4	33.05
SSPM-6	6	36.45
SSPM-8	8	41.75
SSPM-10	10	43.50
SSPM-12	12	47.65



#### Equal Ys

0386	OD mm	£
SSPY-4	4	44.45
SSPY-6	6	46.45
SSPY-8	8	51.70
SSPY-10	10	60.00
SSPY-12	12	70.55

### Stem Connectors



#### Tube x Stem Reducers

0386	OD mm	OD mm	£
SSPGJ6-4	6	4	17.05
SSPGJ8-4	8	4	17.05
SSPGJ8-6	8	6	17.05
SSPGJ10-6	10	6	19.95
SSPGJ10-8	10	8	19.95
SSPGJ12-8	12	8	19.95
SSPGJ12-10	12	10	21.75

### Plug



#### Tube

0386	OD mm	£
SSPP-4	4	6.90
SSPP-6	6	7.05
SSPP-8	8	7.60
SSPP-10	10	8.80
SSPP-12	12	10.00



All seals have FDA Certification

- Hydraulics
- Hydraulic QRC
- Pneumatic QRC
- Ind. Air Prep., Monitor & Test
- KELM™ Pneumatics
- Pneumatic & Vacuum Equipment
- Valves
- Ring Main Systems
- Adaptors & Fittings
- Stainless Steel
- Malleable Iron
- Hose, Tubing & Couplings
- Clamps & Clips
- Sprays & Adhesives
- Blow Guns & Vacuum
- Wash Down & Fuelling
- Air Tools
- Tools, Hardware & PPE