



Pilot Operated General Purpose Solenoid Valves



Page Tech Sheet **10162**

Section 5 – KELM™ Pneumatics

Pressure Range:
0.5 to 10 bar

2/2 Normally Closed



Coils to Suit K225 Normally Closed Valves



- Hydraulics
- Hydraulic QRC
- Pneumatic QRC
- Ind. Air Prep., Monitor & Test
- KELM™ Pneumatics**

- Pneumatic & Vacuum Equipment
- Valves
- Ring Main Systems
- Adaptors & Fittings
- Stainless Steel
- Malleable Iron
- Hose, Tubing & Couplings
- Clamps & Clips
- Sprays & Adhesives
- Blow Guns & Vacuum
- Wash Down & Fuelling
- Air Tools
- Tools, Hardware & PPE

3/8" BSPP

Flow Rate 55 lpm
Orifice 13mm

0366



£

K225-03-230AC-NC	230/50V AC	78.05
K225-03-110AC-NC	110/50V AC	78.05
K225-03-24AC-NC	24/50V AC	78.05
K225-03-24DC-NC	24V DC	78.05
K225-03-12DC-NC	12V DC	78.05

1" BSPP

Flow Rate 160 lpm
Orifice 25mm

0366



£

K225-08-230AC-NC	230/50V AC	140.00
K225-08-110AC-NC	110/50V AC	140.00
K225-08-24AC-NC	24/50V AC	140.00
K225-08-24DC-NC	24V DC	140.00
K225-08-12DC-NC	12V DC	140.00

Coil & Plug

0366



£

K225-230/50AC-NC	230/50V AC	26.80
K225-110/50AC-NC	110/50V AC	26.80
K225-24/50AC-NC	24/50V AC	26.80
K225-24DC-NC	24V DC	26.80
K225-12DC-NC	12V DC	26.80

1/2" BSPP

Flow Rate 63 lpm
Orifice 13mm

0366



£

K225-04-230AC-NC	230/50V AC	88.00
K225-04-110AC-NC	110/50V AC	88.00
K225-04-24AC-NC	24/50V AC	88.00
K225-04-24DC-NC	24V DC	88.00
K225-04-12DC-NC	12V DC	88.00

1.1/4" BSPP

Flow Rate 370 lpm
Orifice 38mm

0366



£

K225-12-230AC-NC	230/50V AC	177.05
K225-12-110AC-NC	110/50V AC	177.05
K225-12-24AC-NC	24/50V AC	177.05
K225-12-24DC-NC	24V DC	177.05
K225-12-12DC-NC	12V DC	177.05

Valve Timer



3/4" BSPP

Flow Rate 100 lpm
Orifice 25mm

0366



£

K225-06-230AC-NC	230/50V AC	104.95
K225-06-110AC-NC	110/50V AC	104.95
K225-06-24AC-NC	24/50V AC	104.95
K225-06-24DC-NC	24V DC	104.95
K225-06-12DC-NC	12V DC	104.95

1.1/2" BSPP

Flow Rate 400 lpm
Orifice 38mm

0366



£

K225-14-230AC-NC	230/50V AC	301.90
K225-14-110AC-NC	110/50V AC	301.90
K225-14-24AC-NC	24/50V AC	301.90
K225-14-24DC-NC	24V DC	301.90
K225-14-12DC-NC	12V DC	301.90

2" BSPP

Flow Rate 540 lpm
Orifice 50mm

0366



£

K225-20-230AC-NC	230/50V AC	334.35
K225-20-110AC-NC	110/50V AC	334.35
K225-20-24AC-NC	24/50V AC	334.35
K225-20-24DC-NC	24V DC	334.35
K225-20-12DC-NC	12V DC	334.35

CE Marked

0366

£

KVT	46.35
-----	-------