



Actuated Process Ball Valves



Actuator Working Temperature:
-20°C to +80°C

Ball Valve Working Temperature:
-20°C to +95°C



Actuator Working Pressure:
2.5 to 8 bar

Ball Valve Maximum Working Pressure:
3/8" 16 bar
1/2" to 2" 40 bar

Actuator

Media:
Dry or lubricated compressed air, to be filtered by a 30µm filter element

Travel Adjustment: ±5° on the rotation 0° and 90°

Ball Valve
Full Bore

Nickel Plated Brass Body Ball Valves

Tech Sheet
10145



Double Acting, Aluminium Actuator, BSPP

0364



£

2184-0000	3/8"	90.95
2184-0001	1/2"	94.25
2184-0002	3/4"	105.25
2184-0003	1"	121.70
2184-0004	1.1/4"	165.50
2184-0005	1.1/2"	227.80
2184-0006	2"	299.05

Nickel Plated Brass Body Ball Valves, WRAS Approved

Tech Sheet
10147



Double Acting, Aluminium Actuator, BSPP

0364



£

2184-0014	1/2"	94.25
2184-0015	3/4"	105.25
2184-0016	1"	121.70
2184-0017	1.1/4"	165.50
2184-0018	1.1/2"	244.30
2184-0019	2"	315.60

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELMK™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

Tech Sheet
10146



Single Acting, Aluminium Actuator, BSPP

0364



£

2184-0007	3/8"	152.75
2184-0008	1/2"	156.05
2184-0009	3/4"	167.05
2184-0010	1"	183.50
2184-0011	1.1/4"	227.30
2184-0012	1.1/2"	326.35
2184-0013	2"	397.60

Tech Sheet
10148



Single Acting, Aluminium Actuator, BSPP

0364



£

2184-0020	1/2"	156.05
2184-0021	3/4"	167.05
2184-0022	1"	183.50
2184-0023	1.1/4"	227.30
2184-0024	1.1/2"	326.35
2184-0025	2"	397.60