



Actuated Process Ball Valves



Actuator Working Temperature:
-20°C to +80°C

Ball Valve Working Temperature:
-20°C to +200°C

Actuator Working Pressure:
2.5 to 8 bar

Ball Valve Maximum Working Pressure:
70 bar (1000psi)

Actuator Media: Dry or lubricated compressed air, to be filtered by a 30µm filter element

Travel Adjustment: ±5° on the rotation 0° and 90°

Ball Valve Full Bore

3 Piece Stainless Steel Body Ball Valves, Socket Weld

Tech Sheet 10153



Double Acting, Aluminium Actuator

0364	Body	£
2184-0064	1/4"	136.80
2184-0065	3/8"	136.80
2184-0066	1/2"	125.45
2184-0067	3/4"	132.35
2184-0068	1"	174.40
2184-0069	1.1/4"	304.15
2184-0070	1.1/2"	236.90
2184-0071	2"	302.00
2184-0072	2.1/2"	765.40
2184-0073	3"	1141.75
2184-0074	4"	1904.90

3 Piece Stainless Steel Body Ball Valves, Butt Weld

Tech Sheet 10155



Double Acting, Aluminium Actuator

0364	Body	£
2184-0086	1/4"	114.80
2184-0087	3/8"	128.65
2184-0088	1/2"	141.40
2184-0089	3/4"	165.70
2184-0090	1"	179.00
2184-0091	1.1/4"	205.40
2184-0092	1.1/2"	236.90
2184-0093	2"	289.95
2184-0094	2.1/2"	765.40
2184-0095	3"	786.30
2184-0096	4"	2401.90

Tech Sheet 10154



Single Acting, Aluminium Actuator

0364	Body	£
2184-0075	1/4"	174.70
2184-0076	3/8"	174.70
2184-0077	1/2"	163.35
2184-0078	3/4"	170.25
2184-0079	1"	217.75
2184-0080	1.1/4"	347.50
2184-0081	1.1/2"	318.95
2184-0082	2"	417.15
2184-0083	2.1/2"	858.50
2184-0084	3"	1373.50
2184-0085	4"	2092.15

Tech Sheet 10156



Single Acting, Aluminium Actuator

0364	Body	£
2184-0097	1/4"	152.70
2184-0098	3/8"	166.55
2184-0099	1/2"	179.30
2184-0100	3/4"	203.60
2184-0101	1"	222.40
2184-0102	1.1/4"	248.75
2184-0103	1.1/2"	318.95
2184-0104	2"	405.10
2184-0105	2.1/2"	858.50
2184-0106	3"	1018.05
2184-0107	4"	2589.10