



Pneufit® Push-In Fittings, Imperial



- For simple and quick assembly of pneumatic circuits
- Positive tube anchorage
- Wide range of types available
- Reliable and corrosion resistant

Medium:

Compressed Air

Collet & Body Manufactured from Bar:

Nickel Plated Brass to BS 2874: 1986 (CZ121)

Body Manufactured from Stamping:

Nickel Plated Brass to BS 2872: 1969 (CZ122)

Seal:

Nitrile Rubber

Tube Sizes:

1/8", 1/4", 3/8", 1/2" O/D

Warning:

The push-in tube fittings in this section must not be used in vehicle air braking and ancillary systems

**Ambient Temperature:**

-20°C to +80°C

**Operating Pressure:**

Vacuum – 18 bar unless otherwise stated (dependant upon tubing specification)

Straight Adaptors



BSPT

Hydraulics	0038	OD	Wavy	£
Hydraulic QRC	121250118	1/8"	1/8"	4.80
	121250418	1/4"	1/8"	4.65
	121250428	1/4"	1/4"	4.90
Pneumatic QRC	121250628	3/8"	1/4"	9.20
	121250638	3/8"	3/8"	10.55

Elbow Connectors



Tube x Tube

0038	OD	£
120400400	1/4"	6.85
120400600	3/8"	12.30

Swivel Tee Adaptor



BSPT

0038	OD	Wavy	£
121670418	1/4"	1/8"	10.50

Straight Connectors



Tube x Tube

0038	OD	£
120200400	1/4"	5.50
120200600	3/8"	9.25

90° Swivel Elbow Adaptors



BSPT

0038	OD	Wavy	£
121470418	1/4"	1/8"	6.10
121470428	1/4"	1/4"	7.05
121470628	3/8"	1/4"	12.35
121470638	3/8"	3/8"	12.05

Tee Connectors



Tube x Tube

0038	OD	£
120600300	3/16"	8.60
120600400	1/4"	8.90
120600600	3/8"	13.35

Bulkhead Connectors



Tube x Tube

0038	OD	Wavy	£
120290400	1/4"	M12 x 1.0	12.40
120290600	3/8"	M20 x 1.5	21.95