



Hydraulic Hose & Fittings



Aeroquip

Port & Connector Identification Kit

Applications:
Accurate identification of ports and connectors is made easy and simple with this kit, allowing correct hose and tube assemblies to be selected and installed.



Metric & Imperial

0235	£
FT1341	126.75

High Pressure Cleaning Hose

Temperature Range:
-40°C to +70°C
(up to +120°C)



Max Working Pressure:
280 bar

Applications:
High pressure cleaning hose for use in the sanitation & cleaning field with non polluting cover. Also, high pressure hydraulic systems with petroleum & water glycol based fluids. High pressure cleaners for food, labour and swimming bath areas.

Construction:
Synthetic NBR rubber tube, 1 wire braid reinforcement; synthetic rubber cover, grey.



Aeroquip GH421, Per Metre

0235	ID mm	OD mm	£
GH421-6	9.5	18	13.30

Hose & Permanent Attached Hose Fittings



Synflex®

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

31BO Medium Pressure Hose

Applications:
General hydraulic. High pressure gas transfer. Chemical transfer.

Construction:
Black polyurethane cover. Braided synthetic fibre reinforcement. Nylon core tube.

Temperature Range:
-40°C to +100°C or to +60°C, with water based or fire resistant fluids



Single Line, 75 Metre Coils

0235	ID	Die Ref.	bar	£
31BO-04	1/4"	4540-30400	207	526.30
31BO-06	3/8"	4540-30600	155	563.65

Applications:
Forklifts working in cold storage areas. General hydraulics. Mobile equipment. Lift truck hydraulic systems. Cold temperature motion control.

Construction:
Black polyester cover. Braided synthetic fibre reinforcement. Polyurethane core tube.

Temperature Range:
-54°C to +100°C or to +60°C max., with water based or fire resistant fluids



Twin Line, 75 Metre Coils

0235	ID	Die Ref.	bar	£
3770-21B2	3/16"	4540-30300	207	828.30
3770-21B3	1/4"	4540-30400	207	982.65
3770-21B4	5/16"	4540-30500	172	1117.40
3770-21B5	3/8"	4540-30600	155	1494.70

37BO Medium Pressure Hose

Applications:
Forklifts working in cold storage areas. General hydraulics. Mobile equipment. Lift truck hydraulic systems. Cold temperature motion control.

Construction:
Black polyester cover. Braided synthetic fibre reinforcement. Polyurethane core tube.

Temperature Range:
-54°C to +100°C or to +60°C max., with water based or fire resistant fluids



Single Line, 75 Metre Coils

0235	ID	Die Ref.	bar	£
37BO-03	3/16"	4540-30300	207	586.70
37BO-04	1/4"	4540-30400	207	653.55
37BO-05	5/16"	4540-30500	172	745.75
37BO-06	3/8"	4540-30600	155	776.20
37BO-08	1/2"	4540-30800	138	1127.40

Applications:
General hydraulics & pneumatic systems. Mobile machinery. Hose retractors & sheave routings. Forklift/mast application.

Construction:
Most Synflex hose can be permanently joined to form Twin-line or Multi-line designs. Hose form flat assembly.

Temperature Range:
-54°C to +100°C or to +60°C max., with water based or fire resistant fluids

Twin Line, 75 Metre Coils

0235	ID	Die Ref.	bar	£
3770-27B2	3/16"	4540-30300	207	1274.80
3770-27B3	1/4"	4540-30400	207	1310.80
3770-27B4	5/16"	4540-30500	172	1556.40
3770-27B5	3/8"	4540-30600	155	1696.50
3770-27B6	1/2"	4540-30800	138	2424.35