



## Hose & Permanent Attached Hose Fittings



### 37AL Non-conductive Constant Pressure Hose

SAE100R7 Non Conductive.

**Applications:**

Electric utility truck hydraulic systems.  
Mobile equipment (picker, utility vehicles).

**Construction:**

Orange non-perforated, non-stick polyurethane cover.  
Braided synthetic fibre reinforcement.  
Polyester core tube.



**Temperature Range:**

-54°C to +100°C or to +66°C, with water based or fire resistant fluids



Single Line, 75 Metre Coils

0235		Die Ref.		£
37AL-04	1/4"	4540-3W400	207	731.70
37AL-06	3/8"	4540-30600	207	920.35

### 3R80 High Pressure Hose

SAE100R8

**Applications:**

General hydraulic systems.  
Hydraulic tools.  
Mobile equipment.  
High pressure pneumatic systems.

High pressure chemical transfer.

**Construction:**

Black perforated polyurethane cover.  
Braided synthetic fibre reinforcement.  
Nylon core tube.



**Temperature Range:**

-40°C to +100°C or to +66°C, with water based or fire resistant fluids



Single Line, 75 Metre Coils

0235		Die Ref.		£
3R80-03	3/16"	4540-H03	345	737.40
3R80-04	1/4"	4540-H04	345	843.00
3R80-06	3/8"	4540-H06	276	1093.75
3R80-08	1/2"	4540-H08	241	1567.65
3R80-12	3/4"	4540-H12	155	2317.10

Single Line, 60 Metre Coils

0235		Die Ref.		£
3R80-16	1"	4540-H16	138	3200.50

### 3E80 Non-conductive High Pressure Hose

SAE100R8

**Applications:**

General hydraulic systems that may contact high voltage sources.  
Aerial equipment.  
Mobile machinery.

Rescue tools.

**Construction:**

Non-conductive marking & colour code.  
Orange polyurethane non-perforated cover.  
Braided synthetic fibre reinforcement.  
Nylon core tube.



**Temperature Range:**

-40°C to +100°C or to +66°C, with water based or fire resistant fluids



Single Line, 75 Metre Coils

0235		Die Ref.		£
3E80-04	1/4"	4540-H04	345	1021.70
3E80-06	3/8"	4540-H06	276	1277.05
3E80-08	1/2"	4540-H08	241	1706.05

### 32GW/33GW Grease Lubrication Hose

**Applications:**

Hand held grease guns.  
Central lubricating systems.  
**Construction:**  
Black polyurethane cover.

Braided synthetic fibre reinforcement bonded to the core tube.  
Nylon core tube (except 33GW: polyester).



**Temperature Range:**

-30°C to +80°C



50 Metre Coils

0235			£
32GW-DN4-JK2	5/32"	400	329.25
33GW-DN400	5/32"	325	207.25

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE