



Valves



Compact Non-return Valves

Temperature Range:
-20°C to +150°C



Maximum Working Pressure: 145 PSI
Cracking Pressure: 0.5 PSI

Brass, Viton Seals, BSPP

0090		£
VFU8.V	1/8"	22.10
VFU4.V	1/4"	25.00
VFU3.V	3/8"	34.40
VFU2.V	1/2"	34.40

Temperature Range:
-10°C to +85°C

Maximum Working Pressure: 145 PSI
Cracking Pressure: 0.5 PSI

Brass, EPDM Seals

0090		£
VFU8.E	1/8"	19.70
VFU4.E	1/4"	21.90
VFU3.E	3/8"	28.30
VFU2.E	1/2"	30.90

Ported Non-return Valves

Temperature Range:
-10°C to +85°C



Maximum Working Pressure: 145 PSI
Cracking Pressure: 0.5 PSI

Brass, NBR Seals, BSPP

0090		£
VUP8.M	1/8"	10.95
VUP4.M	1/4"	13.30

Temperature Range:
-20°C to +150°C

Maximum Working Pressure: 145 PSI
Cracking Pressure: 0.5 PSI

Brass, Viton Seals, BSPP

0090		£
VUP8.VM	1/8"	9.80
VUP4.VM	1/4"	15.20

Temperature Range:
-10°C to +85°C

Maximum Working Pressure: 145 PSI
Cracking Pressure: 0.5 PSI

Brass, EPDM Seals, BSPP

0090		£
VUP8.EM	1/8"	10.05
VUP4.EM	1/4"	12.55

Y Strainer, Brass

• Mesh Size = 1.5mm up to 2" valve

Temperature Range:
0°C to +100°C



Tech Sheet
10302

Y Strainer, Brass, BSPP

0090		£
YS-38	3/8"	9.40
YS-12	1/2"	10.90
YS-34	3/4"	15.10
YS-1	1"	21.60
YS-114	1.1/4"	34.50
YS-112	1.1/2"	44.45
YS-2	2"	71.15
YS-212	2.1/2"	148.80
YS-3	3"	246.15
YS-4	4"	475.85

Strainers for YS Series

Tech Sheet
2032



Stainless Steel AISI 304

0090	To Suit	£
192-38-STRAINER	YS-38	1.15
192-12-STRAINER	YS-12	1.15
192-34-STRAINER	YS-34	1.60
192-1-STRAINER	YS-1	1.75
192-114-STRAINER	YS-114	1.90
192-112-STRAINER	YS-112	2.30
192-2-STRAINER	YS-2	3.05
192-212-STRAINER	YS-212	10.20
192-3-STRAINER	YS-3	15.40
192-4-STRAINER	YS-4	29.15

Globe Valves - Gunmetal/Brass

• BS 5154 PN 20 Series
B. Test Pressures
(Hydraulic): Shell 30 bar. Seat 22 bar.



Tech Sheet
2031

Type 6062, BSPP

0090		£
GBV-12	1/2"	75.80
GBV-34	3/4"	97.80
GBV-1	1"	154.90
GBV-114	1.1/4"	152.70
GBV-112	1.1/2"	261.55
GBV-2	2"	412.25

Shut-off Valves, Brass

Temperature Range:
+30°C to +80°C

Working Pressure:
8-10 bar



Tech Sheet
10024

Tube x Tube

0090		£
EVST-6	6	35.75
EVST-8	8	36.50
EVST-10	10	39.70

Check Valves, Brass

• Minimum opening pressure 0.5psi

Temperature Range:
0°C to +100°C



Tech Sheet
10025

Type CV100, Opens at 20" W.G., BSPP

0090		£
CV100-38	3/8"	10.00
CV100-12	1/2"	10.00
CV100-34	3/4"	14.00
CV100-1	1"	18.55
CV100-114	1.1/4"	27.35
CV100-112	1.1/2"	48.15
CV100-2	2"	67.20
CV100-212	2.1/2"	183.95
CV100-3	3"	275.25
CV100-4	4"	583.00

Temperature Range:
0°C to +100°C

Tech Sheet
10026

Type CV130, Swing Check Valve, BSPP

0089		£
CV130-38	3/8"	11.20
CV130-12	1/2"	10.45
CV130-34	3/4"	18.20
CV130-1	1"	21.90
CV130-114	1.1/4"	31.65
CV130-112	1.1/2"	41.30
CV130-2	2"	58.10
CV130-212	2.1/2"	116.45
CV130-3	3"	163.65
CV130-4	4"	303.70

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE