



Valves



Plastic Ball Valves

Body:
Polypropylene with
NBR Seal



Operating
Pressure:
3.5 bar



Hose Tail x Hose Tail

0270	To Suit Hose I.D. mm	£
18530-1	12	3.30
18530-2	16	3.30
18530-3	20	3.30



Male BSPP x Male BSPP

0270		£
18570-1	1/2"	2.60
18570-2	1/2" x 3/4"	2.60
18570-3	3/4"	2.60



Hose Tail x Female BSPP

0270	To Suit Hose I.D. mm		£
18563-1	16	1/2"	4.75
18563-2	16	3/4"	4.75
18563-3	20	1/2"	4.75
18563-4	20	3/4"	4.75



Hose Tail x Male BSPP

0270	To Suit Hose I.D. mm		£
18560-1	12	1/2"	3.40
18560-2	12	3/4"	3.40
18560-3	16	1/2"	3.40
18560-4	16	3/4"	3.40
18560-5	20	1/2"	3.40
18560-6	20	3/4"	3.40

Plastic Push-in Valves

Suitable for the use in the Food Industry.



Tech Sheet
10327



Tube x Tube

0270	OD mm	£
14330606	6	10.00
14331010	10	10.65
14331212	12	11.00



Tech Sheet
10326



BSPT Male x Tube

0270	OD mm		£
14340613	6	1/4"	9.90
14341017	10	3/8"	10.20
14341221	12	1/2"	10.85

Temperature Range:
30°C to 85°C



Maximum
Pressure:
11 bar



Tech Sheet
10328



BSPP Female 90°

0270	OD mm		£
14350613	6	1/4"	11.30
14351017	10	3/8"	8.20
14351221	12	1/2"	12.20



In-line Mini Filter

0270	OD mm	£
14480606	6	14.70
14480808	8	15.40
14481010	10	16.15
14481212	12	16.95

Customers who bought from this page also purchased **Worm Drive Hose Clamps** – see page 1268

