



## Bronze Valves

### Ball Valves

- Full bore.

**Temperature Range:**  
-10°C to +140°C

**Maximum Working Pressure:**  
40 bar rated

**Tech Sheet**  
**1817**



2 Piece, Lever Handle, BSPT

0205		£
BVBZ345-12	1/2"	22.45
BVBZ345-34	3/4"	28.75
BVBZ345-1	1"	36.80
BVBZ345-114	1.1/4"	72.15
BVBZ345-112	1.1/2"	89.80
BVBZ345-2	2"	138.85

### Y Type Strainers

- BSP Taper F/F ends.

**Temperature Range:**  
-10°C to +180°C

**Maximum Working Pressure:**  
20 bar rated

**Tech Sheet**  
**1821**



PN20 Y Strainer, BSPT

0205		£
YSBZ368-12	1/2"	30.40
YSBZ368-34	3/4"	40.50
YSBZ368-1	1"	63.40
YSBZ368-114	1.1/4"	92.00
YSBZ368-112	1.1/2"	119.75
YSBZ368-2	2"	195.00

### Globe Valves

- BS 5154 approved BSP Taper F/F ends.
- Renewable PTFE seat.

**Temperature Range:**  
-10°C to +198°C

**Maximum Working Pressure:**  
32 bar rated

**Tech Sheet**  
**1818**



PN32 Hand Wheel, BSPT

0205		£
GVBZ350-12	1/2"	55.55
GVBZ350-34	3/4"	81.70
GVBZ350-1	1"	118.25
GVBZ350-114	1.1/4"	164.35
GVBZ350-112	1.1/2"	245.45
GVBZ350-2	2"	373.80

### Swing Check Valves

- BSP Taper F/F ends.

**Temperature Range:**  
-10°C to +180°C

**Maximum Working Pressure:**  
20 bar rated

**Tech Sheet**  
**1822**



PN20 Swing Check Valve, BSPT

0205		£
CVBZ384-12	1/2"	28.60
CVBZ384-34	3/4"	38.90
CVBZ384-1	1"	51.70
CVBZ384-114	1.1/4"	72.80
CVBZ384-112	1.1/2"	95.70
CVBZ384-2	2"	145.10

### Gate Valves

- BS 5154 approved BSP Taper F/F ends.
- Handwheel operation.

**Temperature Range:**  
-10°C to +180°C

**Maximum Working Pressure:**  
20 bar rated

**Tech Sheet**  
**1819**



PN20 Hand Wheel, BSPT

0205		£
GVBZ375HW-12	1/2"	32.20
GVBZ375HW-34	3/4"	39.75
GVBZ375HW-1	1"	54.85
GVBZ375HW-114	1.1/4"	74.25
GVBZ375HW-112	1.1/2"	97.35
GVBZ375HW-2	2"	147.80

- BS 5154 approved BSP Taper F/F lockshield.

**Temperature Range:**  
-10°C to +180°C

**Maximum Working Pressure:**  
20 bar rated

**Tech Sheet**  
**1820**



PN20 Lock Shield, BSPT

0205		£
GVBZ375LS-12	1/2"	33.50
GVBZ375LS-34	3/4"	41.40
GVBZ375LS-1	1"	57.00
GVBZ375LS-114	1.1/4"	77.25
GVBZ375LS-112	1.1/2"	101.15
GVBZ375LS-2	2"	153.70

BS5154B Approved. P.E.D. (Pressure Equipment Directive Compliance) – Suitable for Heating & Ventilation Applications.

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE