



## Ball & Check Valves



### Tech Sheet 10660

#### Adjustable Check Valves



Brass nickel plated

Female, BSPP

1012



LE-7930 10 10	1/8"	1 to 0.10	23.00
LE-7930 13 13	1/4"	1 to 0.10	24.25
LE-7930 17 17	3/8"	1 to 0.15	29.00

#### Adjustable Check Valves, Supply Version



Brass nickel plated

Male x Female, BSPP

1012



LE-7931 10 10	1/8"	1 to 0.10	26.50
LE-7931 13 13	1/4"	1 to 0.10	30.10
LE-7931 17 17	3/8"	1 to 0.15	34.80

#### Adjustable Check Valves, Exhaust Version



Brass nickel plated

Male x Female, BSPP

1012



LE-7932 10 10	1/8"	1 to 0.10	26.50
LE-7932 13 13	1/4"	1 to 0.10	30.10
LE-7932 17 17	3/8"	1 to 0.15	34.80

### Tech Sheet 10320

#### Flow Control Regulators

Stainless steel flow control regulators control the speed of a pneumatic cylinder (models LE-7820 7822) or the speed of a chemical of food fluid carried (model 7822: for fluids compatible with FKM and PTFE seals) in aggressive environments or submitted to high mechanical or chemical constraints.

Designed without retention zones, these models are perfectly suitable for food applications or requiring frequent washing of installations.

**Working Temperature:**  
-15°C to 120°C

**Working Pressure:**  
1 to 16 bar

Tech Sheet 10320



In-line, 1 Way Adjustment, BSPP

1012



LE-7820 00 10	1/8"	72.20
LE-7820 00 13	1/4"	78.60
LE-7820 00 17	3/8"	139.45
LE-7820 00 21	1/2"	141.70

In-line, Bi-directional, BSPP

1012



LE-7822 00 10	1/8"	77.50
LE-7822 00 13	1/4"	125.25
LE-7822 00 17	3/8"	141.70
LE-7822 00 21	1/2"	146.15

#### Non-return Valves

Legris stainless steel non-return valves allow fluids to pass in one direction whilst blocking flow in the other direction. Robust and extremely compact, they are suitable for use as a safety item in all fluids circuits. They

are ideal for use in severe conditions and in aggressive environments.

**Operation:** A stainless steel valve blocks the fluid passage, when the pressure differential is lower than 0.25 bar.



**Working Temperature:**  
-20°C to 180°C



**Working Pressure:**  
0.5 to 40 bar



Uni-directional, Female/Female, BSPP

1012



LE-4890 10 10	1/8"	22	53.10
LE-4890 13 13	1/4"	22	70.85
LE-4890 17 17	3/8"	30	86.30
LE-4890 21 21	1/2"	30	95.30
LE-4890 27 27	3/4"	35	97.55
LE-4890 34 34	1"	42	124.50



Uni-directional, Male/Female, BSPP

1012



LE-4891 10 10	1/8"	22	60.80
LE-4891 13 13	1/4"	22	64.50
LE-4891 17 17	3/8"	30	72.05
LE-4891 21 21	1/2"	30	79.65
LE-4891 27 27	3/4"	35	102.40
LE-4891 34 34	1"	42	130.40



Uni-directional, Female/Male, BSPP

1012



LE-4892 10 10	1/8"	22	60.80
LE-4892 13 13	1/4"	22	64.50
LE-4892 17 17	3/8"	30	72.05
LE-4892 21 21	1/2"	30	79.65
LE-4892 27 27	3/4"	35	102.40
LE-4892 34 34	1"	42	130.40



Uni-directional, Female/Female, NPT

1012



LE-4895 11 11	1/8"	22	55.70
LE-4895 14 14	1/4"	22	59.20
LE-4895 18 18	3/8"	30	72.20
LE-4895 22 22	1/2"	30	79.80

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE