



Ball Valves



Standard 3 Way Ball Valves

Temperature Range:
-20°C to +80°C

Maximum Working Pressure:
20 bar

- L Ported Closed Centre

Tech Sheet
10461



Female Right Angled Porting, BSPP

1012			
------	--	--	--

LE-0482 06 13	1/4"	6	40.40
LE-0482 09 17	3/8"	9	37.75
LE-0482 12 21	1/2"	12	47.20
LE-0482 23 34	1"	23	105.90

- L Ported Closed Centre

Tech Sheet
10464



Female Right Angled Porting - Panel Mountable, BSPP

1012			
------	--	--	--

LE-0448 06 13	1/4"	6	31.65
LE-0448 09 17	3/8"	9	44.35
LE-0448 12 21	1/2"	12	64.60

- L Ported

Tech Sheet
10459



Female Equal Plane Porting - Panel Mountable, BSPP

1012			
------	--	--	--

LE-0452 04 10	1/8"	4	48.50
LE-0452 06 13	1/4"	6	55.50

- L Ported Closed Centre

Tech Sheet
10463



Female Right Angled Porting without Closed Position, BSPP

1012			
------	--	--	--

LE-0483 04 10	1/8"	4	29.10
LE-0483 06 13	1/4"	6	29.20
LE-0483 09 17	3/8"	9	31.50
LE-0483 12 21	1/2"	12	45.70

Lockable Ball Valves

- Legris lockable ball valves have been developed in order to prevent potentially dangerous consequences by unintended operation. Lockable in different positions, this range meets international safety requirements, such as ISO 4414. Lockable ball valves feature a plate fixed to the valve body and a plate attached to the valve stem. When the plates are pad-locked together, the valve handle cannot be moved.

Max Pressure:
40 bar

Tech Sheet
10457



The valves are lockable:

- In both open and closed position, by one padlock: models 0437 and 0439.
- Only in the closed position by up to three padlocks: models 0437 and 0438.

Max Pressure:
40 bar

Tech Sheet
10458



In-line Double Female, BSPP

1012			
------	--	--	--

LE-0432 10 17	3/8"	10	46.80
LE-0432 13 21	1/2"	13	52.50
LE-0432 20 27	3/4"	20	66.65
LE-0432 23 34	1"	23	81.05

Max Pressure:
40 bar

Tech Sheet
10462



In-line Double Female with Vent, BSPP

1012			
------	--	--	--

LE-0437 10 17	3/8"	10	58.50
LE-0437 13 21	1/2"	13	78.20
LE-0437 18 27	3/4"	18	92.45
LE-0437 23 34	1"	23	105.90

Max Pressure:
20 bar

Tech Sheet
10460



Double Female with Vent, BSPP

1012			
------	--	--	--

LE-0439 07 13	1/4"	7	46.50
LE-0439 10 17	3/8"	10	49.75
LE-0439 13 21	1/2"	13	66.40
LE-0439 18 27	3/4"	18	77.25
LE-0439 23 34	1"	23	116.25

Female 3 Way with Sand Blasted Nickel Plated Body, BSPP

1012			
------	--	--	--

LE-0438 12 21	1/2"	12	64.95
---------------	------	----	-------

For Brass Nickel Plated Adaptors see page 557

