



# Safety Valves



## Liquid Relief Valve (Fig 542L)

**Applications:** NABIC Liquid Relief Valves are intended for use where pressure tightness is required on the discharge side of the valve. They are ideal for use on pump relief and bypass relief applications, also on outside installations and where tamper proof units are required.

**Available options are:** Stainless steel springs, high pressure versions and viton seat design.

**Construction:** The valves are of gunmetal construction with top guided copper alloy parts, fitted with chrome vanadium spring as standard they also incorporate the proven NABIC PTFE to metal seating design. O-Ring seals ensure pressure tightness at cover and cap joints.

**Note:** Due to pressure setting and certification of this product normal delivery will be up to 5 working days, manufacturer's stock permitting.

**Request Tech-Sheet No. 1400 for Technical Information.**

**Features:**

- High degree of seat tightness.
- Designed and tested to BS 6759.
- WRAS approved for use on potable water.
- Certified discharge tables.



Section 7 - Valves

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

BSPP

	0115			£	0115			£	0115			£
542L-15-1	1/2"	1	155.45	542L-20-6.5	3/4"	6.5	178.45	542L-32-10.5	1.1/4"	10.5	325.20	
542L-15-1.5	1/2"	1.5	155.45	542L-20-7	3/4"	7	178.45	542L-40-1.5	1.1/2"	1.5	435.55	
542L-15-2	1/2"	2	155.45	542L-20-8	3/4"	8	178.45	542L-40-2.5	1.1/2"	2.5	435.55	
542L-15-2.5	1/2"	2.5	155.45	542L-20-9	3/4"	9	178.45	542L-40-5	1.1/2"	5	435.55	
542L-15-3	1/2"	3	155.45	542L-20-10	3/4"	10	178.45	542L-40-6	1.1/2"	6	435.55	
542L-15-3.5	1/2"	3.5	155.45	542L-25-1	1"	1	236.05	542L-40-7	1.1/2"	7	435.55	
542L-15-4	1/2"	4	155.45	542L-25-1.5	1"	1.5	236.05	542L-40-10	1.1/2"	10	435.55	
542L-15-4.5	1/2"	4.5	155.45	542L-25-2	1"	2	236.05	542L-50-1.5	2"	1.5	549.70	
542L-15-5	1/2"	5	155.45	542L-25-2.5	1"	2.5	236.05	542L-50-2	2"	2	549.70	
542L-15-6	1/2"	6	155.45	542L-25-3	1"	3	236.05	542L-50-4	2"	4	549.70	
542L-15-7	1/2"	7	155.45	542L-25-3.5	1"	3.5	236.05	542L-50-7.5	2"	7.5	549.70	
542L-15-8.5	1/2"	8.5	155.45	542L-25-4	1"	4	236.05	542L-50-8.5	2"	8.5	549.70	
542L-15-10	1/2"	10	155.45	542L-25-5	1"	5	236.05	542L-50-9.5	2"	9.5	549.70	
542L-15-10.5	1/2"	10.5	155.45	542L-25-6	1"	6	236.05	542L-50-10	2"	10	549.70	
542L-20-1	3/4"	1	155.45	542L-25-7	1"	7	236.05	542L-50-10.5	2"	10.5	549.70	
542L-20-1.5	3/4"	1.5	178.45	542L-25-8	1"	8	236.05	542L-65-2	2.1/2"	2	771.90	
542L-20-2	3/4"	2	178.45	542L-25-10	1"	10	236.05	542L-65-3	2.1/2"	3	771.90	
542L-20-2.5	3/4"	2.5	178.45	542L-25-10.5	1"	10.5	236.05	542L-65-3.5	2.1/2"	3.5	771.90	
542L-20-3	3/4"	3	178.45	542L-32-3	1.1/4"	3	325.20	542L-65-5	2.1/2"	5	771.90	
542L-20-3.5	3/4"	3.5	178.45	542L-32-4	1.1/4"	4	325.20	542L-80-4.5	3"	4.5	1105.15	
542L-20-5	3/4"	5	178.45	542L-32-8	1.1/4"	8	325.20	542L-80-7	3"	7	1105.15	
542L-20-6	3/4"	6	178.45	542L-32-10	1.1/4"	10	325.20					

Individual Test Certs to be requested at the time of order