



Safety Valves



Brass Enclosed Safety Valves, Liquid Duty Nominal Bore, 10mm-13mm

Seetru Enclosed Discharge Safety Relief valves are compact and highly efficient. Polymers such as Viton, Nitrile, Silicone, Neoprene and EPDM offer excellent sealing performance. These valves are suitable for a wide range of applications. They are available in stainless steel, dezincification resistant brass or a combination of dezincification resistant brass with stainless steel trim. Type approved and/or designed in accordance with national & international standards which include BS6759 part 2 & 3, ISO4126-1:1991, TUV (Germany) in compliance with AD Merkblatt A2 and BAM (Germany) requirements for oxygen. Compliant with the requirements of the European Pressure Directive 97/23/EC and CE marked. **Oxygen service valves are subject to degreasing at additional cost.** Seals: Viton Sealing: Elastomer



Section 7 - Valves

Maximum Temperature:
180°C

Liquid Duty Only Calculated:
Kg/hr Water @ 15°C

Maximum Temperature:
180°C

Liquid Duty Only Calculated:
Kg/hr Water @ 15°C

Maximum Temperature:
180°C

Liquid Duty Only Calculated:
Kg/hr Water @ 15°C

Tech Sheet 10347

Tech Sheet 10347

Tech Sheet 10346

10mm, 3/8" x 3/4" BSPP Male/Female

10mm, 1/2" x 3/4" BSPP Male/Female

13mm, 3/4" x 1" BSPP Male/Female

0171	Flow	Set	£
SEE9221P2B	2380	1	120.85
SEE9222P2B	2913	1.5	120.85
SEE9223P2B	3364	2	120.85
SEE9224P2B	3761	2.5	120.85
SEE9225P2B	4120	3	120.85
SEE922AP2B	4450	3.5	120.85
SEE922BP2B	4757	4	120.85
SEE922CP2B	5046	4.5	120.85
SEE922DP2B	5319	5	120.85
SEE922EP2B	5579	5.5	120.85
SEE922FP2B	5827	6	120.85
SEE922GP2B	6065	6.5	120.85
SEE922HP2B	6294	7	120.85
SEE9229P2B	6514	7.5	120.85
SEE9228P2B	6728	8	120.85
SEE922JP2B	6935	8.5	120.85
SEE9227P2B	7136	9	120.85
SEE922KP2B	7332	9.5	120.85
SEE922MP2B	7708	10.5	120.85
SEE9226P2B	7889	11	120.85
SEE922NP2B	8067	11.5	120.85
SEE922PP2B	8240	12	120.85
SEE922RP2B	8410	12.5	120.85

0171	Flow	Set	£
SEE9321P2B	2378	1	120.85
SEE9322P2B	2913	1.5	120.85
SEE9323P2B	3364	2	120.85
SEE9324P2B	3761	2.5	120.85
SEE9325P2B	4120	3	120.85
SEE932AP2B	4450	3.5	120.85
SEE932BP2B	4757	4	120.85
SEE932CP2B	5046	4.5	120.85
SEE932DP2B	5319	5	120.85
SEE932EP2B	5579	5.5	120.85
SEE932FP2B	5827	6	120.85
SEE932GP2B	6065	6.5	120.85
SEE932HP2B	6294	7	120.85
SEE9329P2B	6514	7.5	120.85
SEE9328P2B	6728	8	120.85
SEE932JP2B	6935	8.5	120.85
SEE932KP2B	7332	9.5	120.85
SEE932LP2B	7527	10	120.85
SEE932MP2B	7708	10.5	120.85
SEE9326P2B	7889	11	120.85
SEE932NP2B	8067	11.5	120.85
SEE932PP2B	8240	12	120.85
SEE932RP2B	8410	12.5	120.85

0171	Flow	Set	£
SEE9431P2B	4780	1	170.45
SEE9432P2B	5854	1.5	170.45
SEE9433P2B	6759	2	170.45
SEE9434P2B	7557	2.5	170.45
SEE9435P2B	8279	3	170.45
SEE943AP2B	8942	3.5	170.45
SEE943BP2B	9559	4	170.45
SEE943CP2B	10139	4.5	170.45
SEE943DP2B	10687	5	170.45
SEE943EP2B	11204	5.5	170.45
SEE943FP2B	11707	6	170.45
SEE943GP2B	12185	6.5	170.45
SEE943HP2B	12645	7	170.45
SEE9439P2B	13089	7.5	170.45
SEE9438P2B	13518	8	170.45
SEE943JP2B	13934	8.5	170.45
SEE9437P2B	14338	9	170.45
SEE943KP2B	14731	9.5	170.45
SEE943LP2B	15114	10	170.45
SEE943MP2B	15487	10.5	170.45
SEE9436P2B	15852	11	170.45
SEE943NP2B	16208	11.5	170.45
SEE943PP2B	16557	12	170.45
SEE943RP2B	16898	12.5	170.45

18, 20 and 25 nominal bore valves available in 1.1/4" & 1.1/2" sizes.

Ask our technical department for additional information.
Individual Test Certs come as standard with above