



Cast Iron Valves

Page Tech Sheet 10263

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

Art 77 Full Bore Ball Valve, Flanged

- ISO 5211 Direct mounting for actuation
- Brass Ball
- GG25 Cast Iron Body
- PTFE Seals

Temperature Rating:
-10°C to +150°C

Maximum Pressure Rating:
16 bar



ISO 5211, PN16

0205	Flange Size	£
AIVD77100LB	1"	173.20
AIVD77150LB	1.1/2"	231.35
AIVD77200LB	2"	261.80
AIVD77250LB	2.1/2"	338.95
AIVD77300LB	3"	427.65
AIVD77400LB	4"	594.50
AIVD77500LB	5"	1064.40
AIVD77600LB	6"	1432.05
AIVD77800LB	8"	3414.30

Art 235 Gate Valve, Flanged BS5150 & BS EN558-1

- Stainless Steel Stem
- Cast Iron Body
- Bronze Seat Ring

Temperature Rating:
-10°C to +230°C

Maximum Pressure Rating:
16 bar



BS EN 1092-2, PN16

0205	Flange Size	£
ACST235200	2"	326.05
ACST235250	2.1/2"	427.85
ACST235300	3"	498.45
ACST235400	4"	734.85
ACST235500	5"	969.50
ACST235600	6"	1291.00
ACST235800	8"	1329.50
ACST2351000	10"	2310.60
ACST2351200	12"	3619.50

Art 210 Gate Valves, Flanged

- Brass Stem
- Cast Iron Body
- Bronze Seat Ring

Temperature Rating:
-10°C to +150°C

Maximum Pressure Rating:
16 bar



BS 3464, BS 10 Table E & D

0205	Flange Size	£
ACST210200	2"	297.35
ACST210250	2.1/2"	341.65
ACST210300	3"	423.55
ACST210400	4"	659.80
ACST210500	5"	827.40
ACST210600	6"	1227.75
ACST210800	8"	1665.10

Art 170 Swing Check Valve, Flanged

- Cast Iron Body
- Bronze Body Seat Ring
- Bronze Disc Seat Ring

Temperature Rating:
-10°C to +230°C

Maximum Pressure Rating:
16 bar



BS EN 1092-2, PN16

0205	Flange Size	£
ACST170200	2"	275.60
ACST170250	2.1/2"	364.20
ACST170300	3"	471.85
ACST170400	4"	725.40
ACST170500	5"	655.80
ACST170600	6"	1106.40
ACST170800	8"	1467.85
ACST1701000	10"	2635.15
ACST1701200	12"	3482.50

Art 121 Wafer Check Valve

- Cast Iron Body
- Stainless Steel Disc
- EPDM Seals

Temperature Rating:
-10°C to +120°C

Maximum Pressure Rating:
16 bar



Universal Flange Mounting, PN16/10 & ASA 150

0205	Flange Size	£
ACSC121200	2"	79.70
ACSC121250	2.1/2"	128.85
ACSC121300	3"	128.35
ACSC121400	4"	226.85
ACSC121500	5"	263.70
ACSC121600	6"	443.35
ACSC121800	8"	678.55
ACSC1211000	10"	1004.55
ACSC1211200	12"	1583.05

Art 185 Y Strainer, Flanged

- Cast Iron Body
- Stainless Steel Screen

Temperature Rating:
-10°C to +230°C

Maximum Pressure Rating:
16 bar



BS EN 1092-2 PN16

0205	Flange Size	£
ACST185200	2"	171.60
ACST185250	2.1/2"	235.00
ACST185300	3"	290.75
ACST185400	4"	468.80
ACST185500	5"	745.85
ACST185600	6"	807.60
ACST185800	8"	1395.50
ACST1851000	10"	2296.20
ACST1851200	12"	3171.35